
Sikacryl®-621 Fire

DECLARATION OF PERFORMANCE

No. 97397559

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	97397559
2	INTENDED USE/S	EN 15651-1:2012 Sealants for interior application F INT
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 15651-1:2012

Notified body/ies:

Declaration of Performance

Sikacryl®-621 Fire
97397559
2019.01 , ver. 1
1545

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire	NPD	System 4	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 4	
Water tightness and air tightness			
Resistance to flow	≤ 5 mm	System 4	
Loss of volume	≤ 45 %	System 4	
Tensile properties (i.e. elongation) at break at 23 °C	≥ 25 %	System 4	
Durability	Pass	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier
Function: General Manager
At Farum 12 November 2019

Name : Kristian Larsen
Function: Head Sealing and Bonding
At Farum on 12 November 2019



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikacryl®- 621 Fire	EAD 350141-00-1106	26054930
Sikacryl®- 621 Fire	EAD 350454-00-1104	39166102

Declaration of Performance

Sikacryl®-621 Fire
97397559
2019.01 , ver. 1
1545



19

Sika Services AG, Zurich, Switzerland

97397559

EN 15651-1:2012

Sealants for interior application F INT

Water tightness and air tightness

Resistance to flow ≤ 5 mm

Loss of volume ≤ 45 %

Tensile properties (i.e. elongation) at break at 23 °C ≥ 25 %

Durability Pass

dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in the product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1 % (w/w).

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance

Sikacryl®-621 Fire
97397559
2019.01 , ver. 1
1545

3/4

BUILDING TRUST



Sika Danmark A/S
Hirsemarken 5
3520 Farum
Denmark
www.sika.dk

Declaration of Performance

Sikacryl®-621 Fire
97397559
2019.01 , ver. 1
1545

4/4

BUILDING TRUST

