

# Skalflex Flexiklæb

UNIQUE IDENTIFICATION

# **DECLARATION OF PERFORMANCE**

No. 13863273

	CODE OF THE PRODUCT- TYPE:	13863273	
2	INTENDED USE/S	EN 12004-1:2017 Adhesive for ceramic tiles - for internal and external use. Improved deformable cementitious adhesive with reduced slip and extended open time.	
3	MANUFACTURER:	Sika Danmark A/S Industrivej 20 B 8800 Viborg	
4	AUTHORISED REPRESENTATIVE:		
_	CYCTERA/C OF AVCD.		

5 SYSTEM/S OF AVCP: System 3

6a HARMONISED STANDARD: EN 12004-1:2017

Notified body/ies: N/A

## 7 DECLARED PERFORMANCE/S

Performance	AVCP	Harmonised Technical Specification
A1	System 3	
NPD	System 3	
≥ 1 N/mm²	System 3	<del></del>
≥ 1 N/mm²	System 3	
≥ 1 N/mm²	System 3	
≥ 1 N/mm²	System 3	
≥ 0,5 N/mm²	System 3	EN 12004-1:2017
≥ 0,5 N/mm² after not less than 30 min.	System 3	_
≥ 2 mm - < 5 mm	System 3	
	A1  NPD $\geq 1 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2$ $\geq 0.5 \text{ N/mm}^2 \text{ after not less than}$ 30 min.	A1 System 3  NPD System 3  ≥ 1 N/mm² System 3  ≥ 0,5 N/mm² System 3  System 3  System 3

## 8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

N/A

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Name : Name

Function: General Manager
At place on date of issue

Function: Technical manager
At place on date of issue

.....

End of information as required by Regulation (EU) No 305/2011





23

Sika Danmark A/S, Viborg, Denmark

DoP No. 13863273

EN 12004-1:2017

Notified Body N/A

Adhesive for ceramic tiles - for internal and external use

Reaction to fire A1

Adhesion  $\geq 1 \text{ N/mm}^2$ Adhesion after heat ageing  $\geq 1 \text{ N/mm}^2$ Adhesion after water immersion  $\geq 1 \text{ N/mm}^2$ Adhesion after freeze-thaw cycles  $\geq 1 \text{ N/mm}^2$ Reduced slip  $\geq 0.5 \text{ N/mm}^2$ .

Extended open time; adhesion  $\geq 0.5 \text{ N/mm}^2$  after not less than 30 min.

Deformable adhesion; transverse

deformation ≥ 2 mm - < 5 mm

http://dop.sika.com

### **ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

#### **LEGAL NOTE**

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Denmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.



### Sika Denmark A/S

Hirsemarken 5 DK-3520 Farum Denmark www.sika.dk

**Declaration of Performance** 

Skalflex Flexiklæb 13863273 2023.07 , ver. 01 1612

