

Sikafloor®-305 W ESD

DECLARATION OF PERFORMANCE

No. 41112818

1 UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:

41112818

2 INTENDED USE/S

Synthetic resin screed for internal uses

3 MANUFACTURER:

Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland

4 AUTHORISED REPRESENTATIVE:

5 SYSTEM/S OF AVCP:

EN 13813: System 4 (for internal uses)

6a HARMONISED STANDARD:

EN 13813:2002

Notified body/ies:

0921 1508

7 DECLARED PERFORMANCE/S

Tested as a part of a system build-up with Sikafloor®-161, Sikafloor®-327 and Sikafloor®-305 W ESD

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire:	Bfl	System 4	
Release of corrosive substances:	SR	System 4	
Water permeability:	NPD	System 4	
Wear resistance:	≤ AR0,5 ¹⁾	System 4	
Bond strength:	≥ B2,0	System 4	
Impact resistance:	≥ IR12	System 4	EN 13813:2002
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

 $^{^{1)}}$ Min. classification, please refer to the individual test certificate.

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Jochen Grötzinger Function: Research and

Development

Stuttgart, 27.11.2018

Name: Dr. Stefan Kühner Function: Marketing

Stuttgart, 27.11.2018

Name: Dr. Heinz Ephardt Function: Quality control

Stuttgart, 27.11.2018

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product name	Harmonised standard	DoP number
Sikafloor®-305 W ESD	EN 1504-2:2004	14551763





EN 13813: 2002

DoP No. 41112818

Sika Services AG, Zürich, Switzerland

Notified Body 0921, 1508

Synthetic resin screed for internal uses

Reaction to fire:	Bri
Release of corrosive substances:	SR
Wear resistance:	≤ AR0,5
Bond strength:	≥ B2,0
Impact resistance:	≥ IR12

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sikas recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the products suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

FOR FURTHER INFORMATION:

Sika Services AG Telefon +41-58 436 40 40 Tüffenwies 16 Telefax +41-58 436 53 54 8048 Zürich www.sika.ch

Declaration of Performance

Sikafloor®-305 W ESD 41112818 27.11.2018 , ver. 2 1008





27.11.2018 , ver. 2 1008