
Sikasil® WS-605 S

DECLARATION OF PERFORMANCE

No. 63179555

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	63179555
2	INTENDED USE/S	EN 15651-1:2012 Sealants for facade for exterior and interior application F EXT-INT CC
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8048 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15651-1:2012
	Notified body/ies:	1119

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonized Technical Specification
Reaction to fire	Class E	System 3	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	System 3	
Resistance to flow	≤ 3 mm	System 3	
Loss of volume	≤ 10 %	System 3	
Tensile properties (i.e. elongation) at maintained extension after water immersion (elastic)	NF at 100 % Elongation	System 3	
Tensile properties (i.e. at secant tensile modulus) for non-structural low modulus sealants used in joints in cold climate areas (-30°)	≤ 0.9 MPa at 100 % Elongation	System 3	
Tensile properties (i.e. at maintained elongation) for non-structural sealants used in joints in cold climate areas (-30°)	NF at 100 % Elongation	System 3	
Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier
Function: General Manager
At Farum on 10th December 2020



.....

Name : Steffan Petersen
Function: Head Industry
At Farum on 10th December 2020



.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonized technical specification	DoP Number
Sikasil® WS-605 S	EN 15651-2: 2012	75326371

Declaration of Performance
Sikasil® WS-605 S
63179555
2018.11 , ver. 04
1024

Template for translation. Only for internal use



18

Sika Services AG, Zurich, Switzerland

DoP No. 63179555

EN 15651-1:2012

Notified Body 1119

Sealants for facade for exterior and interior application
F EXT-INT CC

Reaction to fire	Class E
Resistance to flow	≤ 3 mm
Loss of volume	≤ 10 %
Tensile properties (i.e. elongation) at maintained extension after water immersion (elastic)	NF at 100 % Elongation
Tensile properties (i.e. at secant tensile modulus) for non-structural low modulus sealants used in joints in cold climate areas (-30°)	≤ 0.9 MPa at 100 % Elongation
Tensile properties (i.e. at maintained elongation) for non-structural sealants used in joints in cold climate areas (-30°)	NF at 100 % Elongation
Durability	Pass

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance

Sikasil® WS-605 S
63179555
2018.11 , ver. 04
1024

Template for translation. Only for
internal use

Sika Danmark A/S
Hirsemarken 5
DK-3520 Farum
Denmark
www.sika.dk

Declaration of Performance
Sikasil® WS-605 S
63179555
2018.11 , ver. 04
1024

4/4

Template for translation. Only for
internal use

BUILDING TRUST

