

ETAG 005



DECLARATION OF PERFORMANCE

ACCORDING ANNEX III OF THE REGULATION (EU) NO 305/2011

Sikalastic®-618 No. 18636122

1	UNIQUE IDENTIFICATION CODE OF PRODUCT-TYPE:	18636122
2	INTENDED USE/S	ETAG 005 Sikalastic®-618 is for use as a liquid-applied roof waterproofing kit to resist the passage of water to the building's internal structure, where Essential Requirements 2 Safety in case of fire, 3 Hygiene, health and the environment and 4 Safety in use of Directive 89/106/EEC, including the aspect of durability, apply.
3	MANUFACTURER:	Sika Services AG Tüffenwies 16 8048 Zürich www.sika.com
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6b	EUROPEAN ASSESSMENT DOCUMENT:	ETAG 005-6:2000
	European Technical Assessment:	ETA-12/0316
	Technical Assessment Body:	British Board of Agrèment
	Notified body/ies:	0836

Declaration of Performance

Sikalastic®-618 18636122 2016.06 , Revision 4

DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
External fire performance Part 1 – 4	B _{Roof} (t1), B _{Roof} (t4)	
Reaction to fire:	Euroclass E	
Categorization by working life:	W2	
Categorization by climatic zones:	M and S	
Categorization by imposed loads:		
most compressible substrate:	P3	ETAG 005
least compressible substrate:	P4	
Categorization by surface Temperature		
Lowest:	TL3	
Highest:	TH4	
Statement on dangerous substances:	None contained	
Slipperiness:	NPD	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:


Name: Anders Beier Function: General Manager

At Farum on 18 June 2020

Name: Kristian Larsen

Function: Head Sealing & Bonding and Roofing

At Farum on 18 June 2020







0836

1148 12 18636122

ETAG 005

Sikalastic®-618 is for use as a liquid-applied roof waterproofing kit to resist the passage of water to the building's internal structure, where Essential Requirements 2 Safety in case of fire, 3 Hygiene, health and the environment and 4 Safety in use of Directive 89/106/EEC, including the aspect of durability, apply.

External fire performance Part 1 – 4	BRoof(t1), BRoof(t4)
Reaction to fire:	Euroclass E
Categorization by working life:	
Categorization by climatic zones:	M and S
Categorization by imposed loads:	
most compressible substrate:	P3
least compressible substrate:	P4
Categorization by surface Temperature Lowest: Highest:	TL3 TH4
Statement on dangerous substances:	None contained
Slipperiness:	NPD

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.



LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S Hirsemarken 5 3520 Farum Denmark

Declaration of Performance Sikalastic®-618 18636122 2016.06, Revision 4

