

BUILDING TRUST

Sikasil[®] C DECLARATION OF PERFORMANCE No. 30189649

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT- TYPE:	30189649
2	INTENDED USE/S	EN 15651-3:2012 For non-structural use in sanitary areas S
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 3
6a	HARMONISED STANDARD:	EN 15651-3:2012
	Notified body/ies:	1213

Declaration of Performance Sikasil® C 30189649 2017.10, ver. 1 1104 7 DECLARED PERFORMANCE/S

Release of chemicals dangerous to	Class E	System 3	
•	NPD		
Water tightness and air tightness			
Resistance to flow	≤ 3 mm	System 3	
Loss of volume	≤ 20 %	System 3	EN 15651-
Tensile properties (i.e. elongation)	NF at 60 % elongation	System 3	3:2012
Microbiological growth	1	System 3	
 Durability	Pass	System 3	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier Function: General Manager At Farum on 12 November 2019

Name : Kristian Larsen Function: Head Sealing and Bonding At Farum on 12 November 2019

BUILDING TRUST

End of information as required by Regulation (EU) No 305/2011



Declaration of Performance Sikasil® C 30189649 2017.10 , ver. 1 1104

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikasil [®] C	EN 15651-1:2012	85547911
Sikasil® C	EN 15651-2:2012	77886887
Sikasil® C	EN 15651-1:2012, EN 15651-2:2012, EN 15651- 3:2012	0205040335000000011104

Declaration of Performance Sikasil[®] C 30189649 2017.10 , ver. 1 1104



14 Sika Services AG, Zurich, Switzerland DoP No. 30189649 EN 15651-3:2012 Notified Body 1213 For non-structural use in sanitary areas S Class E Water tightness and air tightness Resistance to flow ≤ 3 mm Loss of volume ≤ 20 % Tensile properties (i.e. elongation) NF at 60 % elongation			
DoP No. 30189649			
	EN 15651-3:2012		
	Notified Body 1213		
For non-sti	ructural use in sanitary areas S		
Reaction to fire	Class E		
Water tightness and air tightness			
	≤ 3 mm		
Loss of volume	≤ 20 %		
Tensile properties (i.e. elongation)	NF at 60 % elongation		
Microbiological growth	1		
Durability	Pass		

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance Sikasil® C 30189649 2017.10, ver. 1 1104



BUILDING TRUST

Sika Danmark A/S Hirsemarken 5 3520 Farum Denmark www.sika.dk

Declaration of Performance Sikasil® C 30189649 2017.10 , ver. 1 1104

