

Sika MonoTop®-112 MultiUse Repair

DECLARATION OF PERFORMANCE

No. 69245044

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	69245044		
2	INTENDED USE/S	EN 1504-3:2005 Structural and non-structural repair products for concrete for use in buildings and civil engineering works		
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich		
4	AUTHORISED REPRESENTATIVE:			
5	SYSTEM/S OF AVCP:	System 2+		
6a	HARMONISED STANDARD:	EN 1504-3:2005		
	Notified body/ies:	0546		

Sika MonoTop®-112 MultiUse Repair 69245044 2019.10 , ver. 2 1026

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compression strength	R3 class	System 2+	
Chloride ion content	≤ 0.05 %	System 2+	
Adhesive bond	≥ 1.5 MPa	System 2+	
Carbonation resistance	Passes	System 2+	
Elastic modulus	≥ 15 GPa	System 2+	
Thermal compatibility freeze- thaw	≥ 1.5 MPa	System 2+	1504-3:2005
Capillary absorption	≤ 0.5 kg.m-2.h-0.5	System 2+	_
Skid resistance	NPD		
Coefficient of thermal expansion	NPD		_
Reaction to fire	Class A1	System 4	
Dangerous substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.


Signed for and on behalf of the manufacturer by:

Name : Anders Beier

Function: General Manager At Farum on 11 May 2020 Name: Jens Berger

Function: Head Flooring and Refurbishment

At Farum on 11 May 2020







13

Sika Services AG, Zurich, Switzerland

DoP No. 69245044

EN 1504-3:2005

Notified Body 0546

Structural and non-structural repair products for concrete for use in buildings and civil engineering works

 Compression strength
 R3 class

 Chloride ion content
 ≤ 0.05 %

 Adhesive bond
 ≥ 1.5 MPa

 Carbonation resistance
 Passes

 Elastic modulus
 ≥ 15 GPa

 Thermal compatibility freeze- thaw
 ≥ 1.5 MPa

Capillary absorption \leq 0.5.kg.m-2.h-0.5

Reaction to fire Class A1

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.



Sika Danmark A/S

Hirsemarken 5 3520 Farum Danmark www.sika.dk

Declaration of Performance

Sika MonoTop®-112 MultiUse Repair 69245044 2019.10 , ver. 2 1026

