

## PRODUCT DATA SHEET

# SikaSeal®-626 Fire Board+

Fire resistant coated protection board

### DESCRIPTION

SikaSeal®-626 Fire Board+ is a mineral wool based protection board coated with the fire resistant, ablative coating Sikacryl®-625 Fire+. Can be combined with many other Sika passive fire protection products for sealing a wide range of service penetrations.

### USES

- Restores the fire resistance performance of walls and floors which incorporate single and multiple service penetrations
- Can be combined with Sikacryl®-621 Fire+, Sikacryl®-625 Fire+, SikaSeal®-627 Fire Collar+ and SikaSeal®-629 Fire Wrap+

### CHARACTERISTICS / ADVANTAGES

- Up to 4 hours fire resistance
- Easy to install, no need for specialist tools
- For face-fit (pattress-fit) and internal-fit installations
- Provides acoustic insulation
- Tested for a large variety of relevant wall and floor types

### APPROVALS / CERTIFICATES

- CE Marking and Declaration of Performance to European Technical Assessment ETA-21/0887, based on EAD 350454-00-1104:2017 - Fire stopping and fire sealing products, penetration seals
- Fire Resistance EN 13501-2, UL-EU, Certificate No.UL-EU-01214-CPR

### PRODUCT INFORMATION

<b>Composition</b>	Mineral wool based core, acrylic coating on one or two sides
<b>Packaging</b>	Boards individually wrapped in a plastic foil.
<b>Shelf life</b>	6 years from the date of production.
<b>Storage conditions</b>	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.
<b>Density</b>	~160 kg/m <sup>3</sup> (Standard)
<b>Dimensions</b>	Coated board: length 1'200 mm, width 600 mm, thickness 30 mm, 50 mm 1S* or 60mm 2S*. * on stock in DK

# TECHNICAL INFORMATION

## Resistance to fire

Refer to 'Approvals / Certificates', Sikas digitale håndbog for gennemførelser or contact Sika Technical Services for specific information.

## Service temperature

-20 °C min. / +70 °C max.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER INFORMATION

- Sika Application Manual: SikaSeal®-626 Fire Board+
- Sikas digitale håndbog for gennemførelser [Digital håndbog for passiv brandsikring \(sika.com\)](#)

## IMPORTANT CONSIDERATIONS

- Not suitable for load bearing applications.
- SikaSeal®-626 Fire Board+ may only be used for applications and in combination with products it was tested for.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

The substrate must be clean, dry, sound, free from oils, grease, dust and loose or friable particles.

### APPLICATION METHOD / TOOLS

Reference must be made to the relevant Sika Application Manual or contact Sika Technical Services for additional information.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

### Sika Danmark A/S

Hirsemarken 5  
3520 Farum  
Tlf. +45 48 18 85 85  
[www.sika.dk](http://www.sika.dk)



### PRODUCT DATA SHEET

SikaSeal®-626 Fire Board+  
August 2022, Version 01.01  
020517100100000012

SikaSeal-626FireBoard+-en-DK-(08-2022)-1-1.pdf