

Sika MonoTop®-3020

DECLARATION OF PERFORMANCE

No. 26386575

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	26386575
2	INTENDED USE/S	EN 1504-3:2005 Structural and nonstructural repair products for concrete for use in buildings and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ System 4 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-3:2005
	Notified body/ies:	1139

26386575 2020.03 , ver. 1 1029

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Compressive strength	R3	System 2+	
Chloride ion content	≤ 0,05 %	System 2+	
Adhesive Bond	≥ 1,5 MPa	System 2+	EN 1504- 3:2005
Carbonation Resistance	Pass	System 2+	
Elastic Modulus	≥ 15 GPa	System 2+	
Thermal Compatibility (freeze-thaw)	≥ 1,5 MPa	System 2+	
Skid resistance	NPD	System 2+	
Capillary Absorption	≤ 0,5 kg·m ⁻² ·h ^{-0,5}	System 2+	
Reaction to fire	A1	System 4	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anders Beier Function: General Manager

At Farum on 16 March 2022

Name: Lasse Jakobsen

Function: Senior Technical Manager

At Farum on 16 March 2022

End of information as required by Regulation (EU) No 305/2011





20

Sika Services AG, Zurich, Switzerland

26386575

EN 1504-3:2005

Notified Body 1139

Structural and nonstructural repair products for concrete for use in buildings and civil engineering works

Compressive strength R3

Chloride ion content ≤ 0,05 %Adhesive Bond ≥ 1,5 MPaCarbonation Resistance Pass

Elastic Modulus \geq 15 GPa Thermal Compatibility (freeze-thaw) \geq 1,5 MPa

Capillary Absorption $\leq 0.5 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0.5}$

Reaction to fire A1

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.



Sika Danmark A/S

HIrsemarken 5 DK-3520 Farum Denmark www.sika.dk

Declaration of Performance Sika MonoTop®-3020 26386575 2020.03 , ver. 1 1029 Template for translation. Only for internal use

