

PRODUCT DATA SHEET

SikaProof® Tape-150 A

FULLY BONDED, SELF-ADHESIVE TAPE FOR INTERNAL JOINTING OF SIKAPROOF A WATERPROOFING SYSTEM

DESCRIPTION

SikaProof® Tape-150 A is a self-adhesive tape, based on a polyacrylate adhesive on a yellow carrier film coated with the SikaProof A fully bonded system.

USES

SikaProof® Tape-150 A may only be used by experienced professionals.

SikaProof® Tape-150 A is used for sealing transverse overlap joints, connections and details within the SikaProof A membrane system (internal / fleece side) in combination with the SikaProof ExTape-150.

CHARACTERISTICS / ADVANTAGES

- Fully bonded to the concrete structure
- No lateral water underflow (like SikaProof® A system)
- High adhesion and sealing ability, especially in cool and damp conditions
- Easy and fast to install

PRODUCT INFORMATION

Packaging	2 rolls packed in one cardboard box, each roll 25 m long and 150 mm width
Appearance / Colour	Top layer with white fleece and sealant (SikaProof® fully bonded system) coated on a yellow carrier film. Bottom layer with polyacrylate adhesive cover with a white release film.
Shelf life	18 months shelf life from date of production if stored properly in undamaged, unopened, original sealed packaging. (For expiry date see label)
Storage conditions	Dry storage at temperatures from +5 °C up to +30 °C. Protect from direct sunlight, rain, snow, ice, humidity, etc. Store in a horizontal position. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.
Thickness	1.70 mm

SYSTEMS

System Structure	SikaProof® Tape-150 A is a system component for internal jointing of the SikaProof® A membrane system in combination with SikaProof® ExTape-150 for external jointing. For more detailed information please refer to the current Method Statement.
-------------------------	--

APPLICATION INFORMATION

Ambient Air Temperature	minimum +5 °C / maximum +35 °C
Substrate Temperature	Surface to be bonded: Minimum +5 °C, if below appropriate measures must be applied.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface among others is the white fleece layer of SikaProof® A sheet membrane. It must be dry (or slightly damp), clean and free of any materials that could impair adhesion.

APPLICATION METHOD / TOOLS

Apply the SikaProof® Tape-150 A to the fleece side of the SikaProof® A sheet membrane:

- remove the release liner
- adhere the self-adhesive side of the tape to the fleece side of the membrane
- press it firmly using a pressure roller

SikaProof® Tape-150 A is used together with SikaProof® ExTape-150 for easy and secure double bonding of joints and connections.

For more detailed information about the installation method please refer to the Method Statement of the SikaProof® A system.

IMPORTANT CONSIDERATIONS

The SikaProof® Tape-150 A must be used in compliance with the current Method Statement of the SikaProof® A system. It must only be installed by trained and approved Sika contractors.

- Do not install SikaProof® Tape-150 A during continuous or prolonged rain- or snowfall.
- The substrate quality and condition must be fulfilled or appropriate measure must be taken.
- SikaProof® Tape-150 A is not permanently UV resistant.
- Therefore the structural concrete must be placed within 4 weeks (28 days) after the SikaProof® A membrane system is installed.

For more detailed information and guidance refer to the current Method Statement for the SikaProof® A membrane system.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S

Hirsemarken 5
3520 Farum
Tlf. +45 48 18 85 85
www.sika.dk



PRODUCT DATA SHEET

SikaProof® Tape-150 A
December 2019, Version 01.01
020704210220000017

SikaProofTape-150A-en-DK-(12-2019)-1-1.pdf