

---

# Sikagard®-674 Lasur W

---

## DECLARATION OF PERFORMANCE

### No. 26755846

---

1	<b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b>	26755846
2	<b>INTENDED USE/S</b>	Surface protection products – Coating Protection against ingress (1.3) Regulation of the moisture balance (2.2) Increasing electrical resistance (8.2)
3	<b>MANUFACTURER:</b>	Sika Deutschland GmbH Kornwestheimer Str. 103 - 107 70439 Stuttgart
4	<b>AUTHORISED REPRESENTATIVE:</b>	
5	<b>SYSTEM/S OF AVCP:</b>	EN 1504-2: System 2+ (for uses in buildings and civil engineering works)
6a	<b>HARMONISED STANDARD:</b>	EN 1504-2:2004
	Notified body/ies:	1119

## 7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Linear shrinkage:	NPD	System 2+	EN 1504-2:2004
Compressive strength:	NPD	System 2+	
Thermal expansion coefficient:	NPD	System 2+	
Abrasion resistance (Taber test):	weight loss NPD	System 2+	
Cross cut:	NPD	System 2+	
Permeability to CO <sub>2</sub> :	s <sub>d</sub> > 50 m	System 2+	
Water vapor permeability:	Class I	System 2+	
Capillary absorption and permeability to water:	w<0,1 kg/(m <sup>2</sup> x h <sup>0,5</sup> )	System 2+	
Thermal compatibility:	NPD	System 2+	
Resistance to thermal shock	NPD	System 2+	
Chemical resistance:	NPD	System 2+	
Resistance to severe chemical attack:	NPD	System 2+	
Crack bridging ability:	NPD	System 2+	
Impact resistance:	NPD	System 2+	
Adhesion strength by pull off test:	≥ 1,0 (0,7) <sup>1)</sup> N/mm <sup>2</sup>	System 2+	
Reaction to fire:	NPD	System 3	
Skid resistance:	NPD	System 2+	
Artificial weathering:	NPD	System 2+	
Antistatic behavior:	NPD	System 2+	
Adhesion on wet concrete:	NPD	System 2+	
Release of dangerous substances:	NPD	System 2+	

<sup>1)</sup> The value in brackets is the lowest accepted value of any reading.

### Declaration of Performance

Sikagard®-674 Lasur W  
26755846  
30.01.2019 , ver.2  
1182

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -  
SPECIFIC TECHNICAL DOCUMENTATION**


---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

---

Name: Anders Beier  
Function: General Manager  
Farum, 09.06.2021



Name: Jens Berger  
Function: Head Specialized Applicators  
Farum, 09.06.2021



---

End of information as required by Regulation (EU) No 305/2011

**Declaration of Performance**

Sikagard®-674 Lasur W  
26755846  
30.01.2019 , ver.2  
1182



08

EN 1504-2:2004

DoP No. 26755846

Sika Deutschland GmbH, Stuttgart

Notified Body 1119

Surface protection products – Coating: Protection against ingress (1.3)  
Regulation of the moisture balance (2.2) Increasing electrical resistance (8.2)

Permeability to CO <sub>2</sub> :	$s_d > 50$ m
Water vapor permeability:	Class I
Capillary absorption and permeability to water:	$w < 0,1$ kg/(m <sup>2</sup> x h <sup>0,5</sup> )
Adhesion strength by pull off test:	$\geq 1,0$ (0,7) N/mm <sup>2</sup>

<http://dop.sika.com>

#### Declaration of Performance

Sikagard®-674 Lasur W

26755846

30.01.2019 , ver.2

1182

---

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

---

### LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

---


### FOR FURTHER INFORMATION:

Sika Danmark A/S

Hirsemarken 5, DK-3520 Farum  
Denmark

Telefon +45-48 18 85 85

[www.sika.dk](http://www.sika.dk)



### Declaration of Performance

Sikagard®-674 Lasur W

26755846

30.01.2019 , ver.2

1182