

PRODUCT DATA SHEET

DensDeck® Prime Roof Board

Coated glass mat gypsum roof board

DESCRIPTION

DensDeck® Prime Roof Board features a gypsum core with coated glass mat facers that are embedded on the top and bottom of the board.

USES

DensDeck® Prime Roof Board is used as a cover board over thermal insulation in fully adhered, partially adhered or mechanically fastened single ply flat roof build-up.

Please note:

- The Product is not suitable for vertical parapet applications

FEATURES

- Improves resistance to foot traffic and hail damage
- Good wind uplift ratings
- Good resistance to deterioration, warping and job-site damage

PRODUCT INFORMATION

Composition	Core	Gypsum
	Surface	Fibreglass with non-asphaltic coating
Packaging	Packed on a pallet protected with shrink foil.	
	Pallet quantity	30 boards
Appearance and colour	Colour	Dark grey (top and bottom surface)
	Shelf life 5 years from date of production	
Storage conditions	Product must be stored in original unopened and undamaged sealed packaging in dry indoor conditions. If stored outside the boards must be stacked clear of the ground and covered with a polythene sheet or weatherproof tarpaulin. Boards that have become wet must be discarded. Always refer to packaging.	
Dimensions	Width	(1219 ± 3) mm
	Length	(2438 ± 7) mm
	Weight	29 kg per board
Thickness	Thickness	(12.7 ± 0.8) mm

TECHNICAL INFORMATION

Compressive strength	900 psi nominal (approx. 6200 kPa)	(ASTM C473)
Flexural-strength	Longitudinal (MD)	≥ 800 N
	Transversal (CMD)	≥ 700 N
Reaction to fire	A1 (for exposed situations)	(EN 158283-1)
Permeability to water vapour	μ =10.0	(EN 158283-1)
Water absorption	Maximum 5 %	(ASTM C1177)
Thermal resistance	0.16 W/m·K	(EN 158283-1)

APPLICATION INFORMATION

Ambient air temperature	Maximum	+60 °C
	Minimum	-15 °C

SYSTEM INFORMATION

Compatibility	The Product is compatible with the following roofing materials: <ul style="list-style-type: none"> ▪ EPS insulation ▪ XPS insulation ▪ Mineral wool insulation ▪ PIR thermal insulation ▪ Sarnafil® PVC and FPO roof waterproofing membranes ▪ Sikaplan® PVC and FPO roof waterproofing membranes
----------------------	---

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The substrate surface must be uniform, smooth and free of any sharp protrusions or burrs. The substrate must also be clean, dry and free of grease and dust.

APPLICATION

IMPORTANT

Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

IMPORTANT

Exposure to moisture

Exposure to water will negatively impact the performance of the Product. It must be kept dry before, during and after installation.

1. Apply only as many boards as can be covered by roof membrane in the same day.
2. Protect boards from rain penetration during breaks in the construction process.
3. Discard any boards that become wet.

Application below +5 °C

Note: Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations. Note: Installation of ancillary products, such as contact adhesives or cleaners is limited to temperatures above +5 °C. Refer to relevant Product Data Sheets for further information.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.