

SikaProof® FixTape-50

Double-sided adhesive tape, butyl rubber based

Product Description	SikaProof® FixTape-50 is a double-sided adhesive tape, consists of a butyl rubber adhesive that is covered with a release liner.
Uses	SikaProof® FixTape-50 is used for different detailing application of the SikaProof® A system.
Characteristics / Advantages	<ul style="list-style-type: none"> ■ High adhesion of the butyl rubber adhesive ■ High durability ■ Easy and fast to install

Product Data

Form							
Appearance / Colors	White release liner over black butyl rubber adhesive.						
Packaging	5 rolls, packed in one cardboard box						
Dimension	<table border="1" style="width: 100%;"> <tr> <td>Width</td> <td>50 mm</td> </tr> <tr> <td>Length</td> <td>20 m</td> </tr> <tr> <td>Thickness</td> <td>1.50 mm</td> </tr> </table>	Width	50 mm	Length	20 m	Thickness	1.50 mm
Width	50 mm						
Length	20 m						
Thickness	1.50 mm						

Storage	
Storage Conditions / Shelf Life	SikaProof® FixTape-50 rolls have a shelf life of 24 months from date of production if stored properly in unopened undamaged original packaging, in a horizontal position, in dry conditions and at temperatures between +5°C and +30°C. The rolls must be protected from direct sunlight, rain, snow and ice, etc. Do not stack pallets of the rolls on top of each other, or under pallets of any other materials during transport or storage.

Technical Data

Compatibility	Not suitable for use in direct contact with tar, asphalt, hot bitumen, wood preservatives with substances containing oil, solvents or any other de-bonding agents. For other material in direct contact (such as any synthetics etc.) the compatibility has to be proved.
----------------------	---



System Information

Accessory	SikaProof® FixTape-50 is an ancillary product for the SikaProof® A sheet membrane waterproofing system.
------------------	---

Application Details

Substrate quality	The contact surfaces must be dry, clean and free of materials that could impair adhesion.
--------------------------	---

Application Conditions /

Limits

Substrate temperature	+5° C min. / +35 °C max.
------------------------------	--------------------------

Ambient air temperature	+5° C min. / +35 °C max.
--------------------------------	--------------------------

Application Instructions

Application Method	<p>SikaProof® FixTape-50 is a cold-applied double-sided adhesive tape for different detailing application.</p> <p>For further more detailed information about the installation method, please refer to the SikaProof® A membrane Product Data Sheet and the Method Statement.</p>
---------------------------	---

Notes on Application / Limitations	<p>The SikaProof® A system must only be installed by trained and approved Sika contractors.</p> <p>SikaProof® FixTape-50 is not UV stabilised and can not be installed on structures permanently exposed to UV light and weathering.</p> <p>Do not apply the SikaProof® FixTape-50 during continuous or prolonged rainfall.</p>
---	---

Value Base

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Local Restrictions

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

Ecology, Health and Safety Information

A Material Safety Data Sheet following EC- Regulation 1907/2006, Article 31 is not required to bring this product to the market, to transport, or to use it. The product does not damage the environment when used as specified.

REACH

Editorial note for National Data Sheets:

(This part highlighted in yellow must be deleted during preparation of National Product Data Sheets)

The following information must be provided automatically and without prompting to industrial and professional users and distributors in any country in which REACH regulations are applicable (Article 33.1):

European Community Regulation on chemicals and their safe use (REACH: EC 1907/2006)

This product is an article within the meaning of Regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. Therefore, there are no registration requirements for substances in articles within the meaning of Article 7.1 of the Regulation.

Based on our current knowledge, this product does not contain SVHC (substances of very high concern) from the list published by the European Chemicals Agency in concentrations above 0.1 % (w/w).

Legal Notes

"Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not updated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise."



Sika Danmark A/S
 Praestemosevej 2-4
 DK-3480 Fredensborg
 Denmark

Phone +45 48 18 85 85
 Telefax +45 48 18 84 96
 e-mail: sika@dk.sika.com
 www.sika.com

