

PRODUCT DATA SHEET

Sika ViscoFlow®-28

Workability enhancing admixture

DESCRIPTION

Sika ViscoFlow®-28 is a PCE-based workability enhancing admixture for ready-mixed concrete.

USES

- Production of ready-mix concrete
- Suitable for most concrete Types

FEATURES

- Strong enhancing of workability time
- Ideal slump-life
- Suitable for many applications

CERTIFICATES AND TEST REPORTS

in preparation:

EN 934-2:T2

Plastisizer and superplastisizer for the production of concrete

Complies with the requirements of the ZTV-ING

PRODUCT INFORMATION

Composition	Polycarboxylate ether
Packaging	Drum: 200 kg Container: 1000 kg Bulk: > 6 t
Appearance and colour	Fluid / colorless
Shelf life	Minimum of 1 year in sealed containers
Storage conditions	Protect against frost, strong sunlight and contamination. Utilise clean tanks and containers when delivered in bulk.
Density	1.036 g/cm³ at 20°C
pH-Value	approx. 5
Solid content	20 % ± 1 % (weight)
Total chloride ion content	< 0.10 %
Equivalent sodium oxide	< 0.5 %

APPLICATION INFORMATION

Recommended dosage	0.3 - 1.4 % bwoc Initial test according to DIN EN 206-1/DIN 1045-2 is required.
---------------------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S
Hirsemarken 5
3520 Farum
Tlf. +45 48 18 85 85
www.sika.dk



PRODUCT DATA SHEET

Sika ViscoFlow®-28
January 2026, Version 02.01
021301011000003936

SikaViscoFlow-28-en-DK-(01-2026)-2-1.pdf

BUILDING TRUST

