

**BUILDING TRUST** 

## PRODUCT DATA SHEET

# SikaForce<sup>®</sup>-096 Cleaner

(formerly SikaForce®-7260 Cleaner)

## Cleaning liquid for tools and application equipment

### TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)

Chemical base		Dipropylene glycol ether
Density		0.97 g/cm <sup>3</sup>
Viscosity	Z3 DIN, shear rate 50 s <sup>-1</sup>	3.5 mPa·s <sup>A</sup>
Vapor pressure		0.4 mm Hg/25 °C
Boiling point		190 °C
Flash point		79 °C
Shelf life		12 months
CQP = Corporate Quality Procedure	<sup>A)</sup> 23 °C / 50 % r.h.	•

#### DESCRIPTION

SikaForce®-096 Cleaner is a liquid with high boiling point for removing of non-cured 1and 2-component polyurethane products • Neutralies the isocyanate groups in polyfrom tools and application equipment.

#### **PRODUCT BENEFITS**

- Not classified
- Safe to use
- urethane products

#### AREAS OF APPLICATION

SikaForce®-096 Cleaner is used for cleaning of tools and flushing of application equipment after dispensing SikaForce adhesives. This product is suitable for experienced professional users only.

PRODUCT DATA SHEET SikaForce®-096 Cleaner Version 02.01 (08 - 2021), en\_DK 019404010960001000

#### METHOD OF APPLICATION

Only uncured 1- and 2-component polyurethane products can be removed with Sika-Force®-096 Cleaner.

Provide adequate ventilation. If SikaForce®-096 Cleaner is processed at temperatures > 30 °C use a local extraction system.

Clean tools by using a brush. If necessary, immerse parts in the SikaForce®-096 Cleaner prior the cleaning process.

For 2-component equipment, it is recommended flushing with recirculation.

#### **STORAGE CONDITIONS**

SikaForce®-096 Cleaner has to be kept between 10 °C and 30 °C in a tightly closed packaging and stored in a well-ventilated storage room.

Minimum temperature during transportation is -20 °C for max. 7 days.

#### FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Copies of the following publications are available on request:

Safety Data Sheets

#### **BASIS OF PRODUCT DATA**

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

#### HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

#### DISCLAIMER

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

PRODUCT DATA SHEET SikaForce®-096 Cleaner Version 02.01 (08 - 2021), en\_DK 019404010960001000 Sika Danmark A/S Hirsemarken 5 3520 Farum Tlf. +45 48 18 85 85 www.sika.dk