

Sikafloor®-144

DECLARATION OF PERFORMANCE

No. 10870067

1 UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:

10870067

2 INTENDED USE/S

Synthetic resin screed for internal uses

3 MANUFACTURER:

Sika Deutschland GmbH Kornwestheimer Str. 103 - 107

70439 Stuttgart

4 AUTHORISED REPRESENTATIVE:

5 SYSTEM/S OF AVCP:

EN 13813: System 4 (for internal uses)

6a HARMONISED STANDARD:

EN 13813:2002

Notified body/ies:

0921 0767

7 DECLARED PERFORMANCE/S

Tested as a part of a system build-up with Sikafloor®-144 underneath Sikafloor®-266 CR filled with 40% of quartz sand 0.1-0.3mm.

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Reaction to fire:	E _{fl} ¹⁾	System 4	
Release of corrosive substances:	SR	System 4	
Water permeability:	NPD	System 4	
Wear resistance:	≤ AR1 ²⁾	System 4	
Bond strength:	≥ B2,0	System 4	
Impact resistance:	≥ IR4	System 4	EN 13813:2002
Sound insulation:	NPD	System 4	
Sound absorption:	NPD	System 4	
Thermal resistance:	NPD	System 4	
Chemical resistance:	NPD	System 4	

 $^{^{1)}}$ According to Commission Decision 2010/85/EU of 9 February 2010 the product fulfils the reaction-to-fire performance class E/E_{fl} without further testing

²⁾ Min. classification, please refer to the individual test certificate.

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anders Beier Function: General Manager At Farum on 06 April 2020 Name: Jens Berger Function: Head Flooring and Refurbishment At Farum on 06 April 2020

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product name	Harmonised standard	DoP number
Sikafloor®-144	EN 1504-2:2004	30413527

	08
DI	N EN 13813:2002
De	oP No. 10870067
Sika Deut	schland GmbH, Stuttgart
Notif	ied Body 0921, 0767
Synthetic res	sin screed for internal uses
·	siii screed for internal uses
Reaction to fire:	Efl
Reaction to fire:	Efi
Reaction to fire: Release of corrosive substances:	E _{fl} SR

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise..

FOR FURTHER INFORMATION:

Sika Danmark A/S Telefon 48 18 85 85
Hirsemarken 5
3520 Farum www.sika.dk

Declaration of Performance Sikafloor®-144 10870067 27.06.2018 , ver. 2 1008

