

## PRODUCT DATA SHEET

# Sarnavap® Tape F

Butyl rubber adhesive tape for Sarnavap® vapour control layers

### DESCRIPTION

Sarnavap® Tape F is a butyl rubber, double-sided adhesion sealing tape with a controlled stretch range.

### USES

This product may only be used by experienced professionals.

- Taping lap splices in Sarnavap® vapour control layers (polyethylene) based material and for attaching Sarnavap® VCL to smooth surfaces.

### CHARACTERISTICS / ADVANTAGES

- Finger-lift release liner
- Controlled adhesive stretch range
- High durability
- Used only at airtight level

### PRODUCT INFORMATION

<b>Composition</b>	Adhesive: Butyl rubber Release liner: Polypropylene
<b>Packaging</b>	Please contact our customer service, for information of what packaging sizes are sold in Denmark.
<b>Appearance / Colour</b>	Smooth flat profile. Black
<b>Shelf life</b>	2 years from date of production
<b>Storage conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.
<b>Length</b>	40,00 m (-5 cm / +20 cm)
<b>Width</b>	15 mm (±1,0 mm)
<b>Thickness</b>	1,0 mm (-0 mm / +0,2 mm) Density: 1,2 g/cm <sup>3</sup> (+20 °C)

### SYSTEMS

<b>System structure</b>	Compatible system products: <ul style="list-style-type: none"> <li>▪ Sarnavap® PE vapour control layer</li> </ul>
<b>Compatibility</b>	Not compatible in direct contact with PVC, tar, asphalt, hot bitumen, wood preservatives with surfactants and substances containing oil, solvents or wetting agents. These materials could adversely affect the product proper-

## APPLICATION INFORMATION

<b>Ambient air temperature</b>	Condition tape in application environment temperature before applying. For seams and detailing min. + 5° C / max. + 40° C
<b>Substrate temperature</b>	+ 5° C / max. + 40° C

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The contact surfaces must be dry, clean and free from dust, grease and other materials which could affect adhesion.

### SUBSTRATE PREPARATION

All dust and loose particles must be completely removed from all surfaces before application of tape.

### APPLICATION METHOD / TOOLS

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

#### Overlaps

Adjoining sheets must overlap 80 mm.

## FURTHER INFORMATION

- Installation instructions: Sarnafil® and Sikaplan® flat roof systems

## IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained and approved contractors, experienced in this type of application.

- The use of Sarnavap® Tape F is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.
- Do not use if exposed to permanent UV

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

Sika Danmark A/S  
Hirsemarken 5  
3520 Farum  
Tlf. +45 48 18 85 85  
www.sika.dk



PRODUCT DATA SHEET  
Sarnavap® Tape F  
October 2020, Version 01.01  
02094505120000002

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## ECOLOGY, HEALTH AND SAFETY

### REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

## LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

SarnavapTapeF-en-DK-(10-2020)-1-1.pdf