



EN 13963
 EN 15824

11
 12

0402


DECLARATION OF PERFORMANCE

Sika® Filler-103

01	03	04	02	001	0	000011	1084
----	----	----	----	-----	---	--------	------

1. Product Type: Unique identification code of the product-type:	Sika® Filler
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	-103, batch nr refer to packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Waterborne multipurpose medium coarse surface light filler. Indoor fine spackling of concrete, gypsum, fabric, wallpaper etc. Especially suited for joint levelling with paper strip
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika® Filler Sika Denmark A/S Præstemosevej 2-4 DK-3480 Fredensborg
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (refer to item 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 4
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	0402 Notified test body 0402 issued under AVCP system 4 tests to EN 13963: fire tests According To EN13823 (SBI method) test report no. P602832 Reaction to fire classification report of product "joint filler 5%" test report no. P602832A. Heat of combustion According To EN ISO 1716. Test reports P602832-01A Rev., P602832-01B/rev and F622673. 0402 Notified test body 0402 issued under AVCP system 4 tests to EN 15824: Fire test according to EN 13823, 2002 (SBI method) and ignitability according To EN ISO 11925-2. Test report Nr.PX05926, PX18221rev2 Reaction to fire classification report PX18221-1rev1

Declaration of Performance



8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Not relevant (refer to item 7)

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Bending Tensile strength	>320 N	EN 13963	EN 13963
Reaction to fire:	A2-s 1,d0	EN 13501-1	
Adhesion	>0,3 MPa	EN 1542	EN 15824
Reaction to fire:	B-s 1,d0	EN 13501-1	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Jimmy Kahl

Product engineer



Patrik Horisberger

General Manager

20 December 2013, Fredensborg

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

"Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise."



For further Information:
Sika Danmark A/S
Præstemosevej 2-4
DK-3480 Fredensborg
Danmark

Phone. +45 48 18 85 85
Telefax +45 48 18 84 96
www.sika.dk