

## PRODUCT DATA SHEET

# Sikacryl<sup>®</sup>-625 Fire

### FIRE RESISTANT ABLATIVE COATING FOR SIKASEAL<sup>®</sup>-626 FIRE BOARD

#### DESCRIPTION

Sikacryl<sup>®</sup>-625 Fire is a 1-part fire resistant, ablativ acrylic coating used for the installation of SikaSeal<sup>®</sup>-626 Fire Board

#### CHARACTERISTICS / ADVANTAGES

- 1-part ready to use, easy to apply, easy to clean
- Provides a neat finish to the cut edges of SikaSeal<sup>®</sup>-626 Fire Board

#### USES

- Touching up SikaSeal<sup>®</sup>-626 Fire Board after installation
- Edge coating of SikaSeal<sup>®</sup>-626 Fire Board when installed on the outer face of a wall or floor

#### PRODUCT INFORMATION

<b>Composition</b>	Water based acrylic
<b>Packaging</b>	5 kg container.
<b>Appearance / Colour</b>	White
<b>Shelf life</b>	12 months from the date of production.
<b>Storage conditions</b>	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.
<b>Density</b>	~1,40 kg/l (ISO 1183-1)

#### TECHNICAL INFORMATION

<b>Resistance to Fire</b>	Refer to SikaSeal <sup>®</sup> -626 Fire Board 'Approvals / Certificates', Sika Passive Fire Protection Handbook or contact Sika Technical Services for specific information.
---------------------------	---

#### APPLICATION INFORMATION

<b>Layer Thickness</b>	2 mm (wet film thickness)
<b>Ambient Air Temperature</b>	+5 °C min. / +40 °C max.
<b>Substrate Temperature</b>	+5 °C min. / +40 °C max., min. 3 °C above dew point temperature

## APPLICATION INSTRUCTIONS

### APPLICATION

Reference must be made to the Sika Passive Fire Protection Handbook or contact Sika Technical Services for specific information.

### CLEANING OF EQUIPMENT

Clean all tools and application equipment with water immediately after use. Hardened material can only be removed mechanically.

### FURTHER INFORMATION

- Sika Method Statement: SikaSeal®-626 Fire Board
- Sika Passive Fire Protection Handbook

### IMPORTANT CONSIDERATIONS

- Limitations regarding dimensions and configuration described in the relevant fire resistance classification reports must be considered.

### BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

### LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

### LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S  
Hirsemarken 5  
3520 Farum  
Tlf. +45 48 18 85 85  
www.sika.dk



PRODUCT DATA SHEET  
Sikacryl®-625 Fire  
January 2020, Version 01.01  
020515110000000002

Sikacryl-625Fire-en-DK-(01-2020)-1-1.pdf