

Sikafloor[®]-150

DECLARATION OF PERFORMANCE

No. 70522070

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	70522070
2	INTENDED USE/S:	Surface protection products – Coating Protection against ingress (1.3) Regulation of the moisture balance (2.2) Physical resistance (5.1) Resistance to chemicals (6.1) Increasing electrical resistance (8.2)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich Switzerland
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	EN 1504-2: System 2+ (for uses in buildings and civil engineering works) EN 1504-2: System 4 (for uses subject to reaction to fire regulations)
6a	HARMONISED STANDARD:	EN 1504-2:2004
	Notified body/ies:	0921

Declaration of Performance

Sikafloor[®]-150
70522070
21.02.2019 , ver. 2
1008

7 DECLARED PERFORMANCE/S		Tested systems: Primer Sikafloor®-150 underneath Sikafloor®-264 N (+ 70% quartz sand F34)	
Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Linear shrinkage:	NPD	System 2+	EN 1504-2:2004
Compressive strength:	NPD	System 2+	
Thermal expansion coefficient:	NPD	System 2+	
Abrasion resistance (Taber test) ¹⁾ :	weight loss < 3000 mg	System 2+	
Cross cut:	NPD	System 2+	
Permeability to CO ₂ :	s _d > 50 m	System 2+	
Water vapor permeability:	Class II	System 2+	
Capillary absorption and permeability to water:	w < 0,1 kg/(m ² x h ^{0,5})	System 2+	
Thermal compatibility:	NPD	System 2+	
Resistance to thermal shock	NPD	System 2+	
Chemical resistance:	NPD	System 2+	
Resistance to severe chemical attack ²⁾ :	Class II	System 2+	
Crack bridging ability:	NPD	System 2+	
Impact resistance:	Class I	System 2+	
Adhesion strength by pull off test:	≥ 2,0 (1,5) ³⁾ N/mm ²	System 2+	
Reaction to fire:	E _{fi}	System 4	
Skid resistance:	NPD	System 2+	
Artificial weathering:	NPD	System 2+	
Antistatic behavior:	NPD	System 2+	
Adhesion on wet concrete:	NPD	System 2+	
Release of dangerous substances:	NPD	System 2+	

¹⁾ Additionally the requirements according to EN 13813 have to be fulfilled

²⁾ Please refer to the Sikafloor Chemical Resistance Chart

³⁾ Rigid systems; the value in brackets is the lowest accepted value of any reading.

Declaration of Performance

Sikafloor®-150
70522070Sikafloor®-150
21.02.2019 , ver. 2
1008

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier
Function: General Manager
At Farum on 06 April 2020



Name : Jens Berger
Function: Head Flooring
and Refurbishment
At Farum on 06 April 2020



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product name	Harmonised standard	DoP number
Sikafloor®-150	EN 13813:2002	73067424

Declaration of Performance

Sikafloor®-150
70522070Sikafloor®-150
21.02.2019 , ver. 2
1008



19

EN 1504-2:2004

DoP No. 70522070

Sika Services AG, Zürich, Switzerland

Notified Body 0921

Surface protection products – Coating: Protection against ingress (1.3)
Regulation of the moisture balance (2.2) Physical resistance (5.1)
Resistance to chemicals (6.1) Increasing electrical resistance (8.2)

Abrasion resistance (Taber test):	weight loss < 3000 mg
Permeability to CO ₂ :	$s_d > 50$ m
Water vapor permeability:	Class II
Capillary absorption and permeability to water:	$w < 0,1$ kg/(m ² x h ^{0,5})
Resistance to severe chemical attack:	Class II
Impact resistance:	Class I
Adhesion strength by pull off test:	$\geq 2,0$ (1,5)N/mm ²
Reaction to fire:	E _{fl}

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance

Sikafloor®-150
70522070Sikafloor®-150
21.02.2019 , ver. 2
1008

FOR FURTHER INFORMATION:

Sika Danmark A/S
Hirsemarken 5
3520 Farum

Telefon 48 18 85 85

www.sika.dk

Declaration of Performance

Sikafloor®-150
70522070Sikafloor®-150
21.02.2019 , ver. 2
1008



Declaration of Performance
Sikafloor®-150
70522070Sikafloor®-150
21.02.2019 , ver. 2
1008

6/6

BUILDING TRUST

