

Sikadur®-31 SBA S-07

DECLARATION OF PERFORMANCE

No. 64946616

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	64946616
2	INTENDED USE/S	EN 1504-4:2004 Structural bonding product for bonded plate reinforcement for use in buildings and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-4:2004
	Notified body/ies:	0921, 0767

Sikadur®-31 SBA S-07 64946616 2018.08, ver. 2 1001

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Bond/adhesion strength	NPD		
Shear adhesion	≥ 12 N/mm²	System 2+	EN 1504- 4:2004
Workability	30 min	System 2+	
Shrinkage/expansion	≤ 0.1 %	System 2+	
Modulus of elasticity	≥ 2000 N/mm ²	System 2+	
Coefficient of thermal expansion	≤ 100 × 10 ⁻⁶ per K	System 2+	
Glass transition temperature	≥ 40 °C	System 2+	
Reaction to fire	Class E	System 3	
Durability	Pass	System 2+	
Dangerous substances	NPD		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Anders Beier General Manager Farum on 12 November 2019 Lasse Jakobsen Senior Technical Manager Farum on 12 November 2019







08

Sika Services AG, Zurich, Switzerland

DoP No. 64946616

EN 1504-4:2004

Notified Body 0921, 0767

Structural bonding product for bonded plate reinforcement for use in buildings and civil engineering works

Shear adhesion ≥ 12 N/mm²

Workability 30 min Shrinkage/expansion $\leq 0.1 \%$

Modulus of elasticity $\geq 2000 \text{ N/mm}^2$ Coefficient of thermal expansion $\leq 100 \times 10^{-6} \text{ per K}$

Glass transition temperature \geq 40 °C Reaction to fire Class E Durability Pass

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

"Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the echnological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Denmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise."



Sika Danmark A/S

Hirsemarken 5 3520 Farum Denmark www.sika.dk

Declaration of Performance

Sikadur®-31 SBA S-07 64946616 2018.08 , ver. 2 1001

