

PRODUCT DATA SHEET

SikaSeal®-626 Fire Board

FIRE RESISTANT COATED PROTECTION BOARD

DESCRIPTION

SikaSeal®-626 Fire Board is a mineral wool based protection board coated with the fire resistant, ablativ coating Sikacryl®-625 Fire on both sides. Its versatility lets it be combined with many other Sika passive fire protection products for sealing a wide range of installation service penetrations.

USES

- Restores the fire resistance performance of floors or walls which incorporates single and multiple installation service penetrations
- Can be combined with Sikacryl®-621 Fire, SikaSeal®-623 Fire, Sikacryl®-624 Fire, SikaSeal®-627 Fire Collar, SikaSeal®-628 Fire Wrap and SikaSeal®-629 Fire Wrap

CHARACTERISTICS / ADVANTAGES

- For face-fit (pattress-fit) and internal-fit installations
- Can be used for penetrations up to 1200 × 730 mm
- Acoustic insulation
- Easy to install, no need for specialist tools
- Up to 4 hours fire resistance

APPROVALS / CERTIFICATES

- CE Marking and Declaration of Performance to European Technical Assessment ETA 18/1048, based on EAD 350454-00-1104:2017 - Fire stopping and fire sealing products, penetration seals
- Fire Board and Coating BS 476, EN 1366-3, SikaSeal®-626 Fire Board, warringtonfire, Approval No. CF 5717
- Fire Board for Fire Stopping EN 1366-1, EN 1366-3, EN 13501-2, EN 13501-3, ETAG 026-2, SikaSeal®-626 Fire Board, UL, Certificate No. UL-EU-01093-CPR
- Fire Resistance Performance Classification EN 13501-2, SikaSeal®-626 Fire Board, warringtonfire, Classification report No. 401159/D

PRODUCT INFORMATION

Packaging	Boards individually wrapped in a plastic foil. 30 boards on a pallet.
Shelf life	5 years from the date of production.
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between -20 °C and +70 °C. Always refer to packaging.
Density	~140 kg/m ³ (EN 1602)
Dimensions	Coated board ~1 200 × 600 × 50 mm Coating thickness ~2 mm

TECHNICAL INFORMATION

Resistance to Fire

Refer to 'Approvals / Certificates', Sika Passive Fire Protection Handbook or contact Sika Technical Services for specific information.

Service Temperature

-20 °C min. / +70 °C max.

APPLICATION INSTRUCTIONS**APPLICATION METHOD / TOOLS**

Reference must be made to the Sika Method Statement: SikaSeal®-626 Fire Board

FURTHER INFORMATION

- Sika Method Statement: SikaSeal®-626 Fire Board
- Sika Passive Fire Protection Handbook
- Fire resistance classification reports

IMPORTANT CONSIDERATIONS

- Limitations regarding dimensions and configuration described in the relevant fire resistance classification reports must be considered.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

ECOLOGY, HEALTH AND SAFETY**REGULATION (EC) NO 1907/2006 - REACH**

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

Sika Danmark A/S

Hirsemarken 5
3520 Farum
Tlf. +45 48 18 85 85
www.sika.dk

**PRODUCT DATA SHEET**

SikaSeal®-626 Fire Board
February 2020, Version 02.01
02051510000000012

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

SikaSeal-626FireBoard-en-DK-(02-2020)-2-1.pdf