

Sikafloor®-3000

Declaration of Performance

No 38327385

1	Unique identification code of the product-type:	38327385		
2	Intended use/es:	For internal uses subject to reaction to fire regulations — Synthetic resin screed material All other uses — Synthetic resin screed material		
3	Manufacturer: Sika Services AG			
		Tüffenwies 16		
		8064 Zürich		
		Switzerland		
5	System/s of AVCP:	System 3 (For internal uses subject to reaction to fire regulations) System 4 (All other uses)		
6a	Harmonised standard:	EN 13813:2002		
	Notified body/ies:	1611, 0921		

1/3

7 Declared performance/s:					
Essential Characteristics	Performance		AVCP	Harmonised Technical Specification	
Reaction to fire	Class B _{fi} -s1		System 3		
Release of corrosive sub- stances	SR		System 4		
Water permeability	NPD		System 4		
Mechanical resistance	Wear resistance	AR0,5	System 4	3813:2002	
	Bond strength	B2,0		313:	
	Impact resistance	IR4		\vdash	
Sound insulation NPD			System 4	_	
Sound absorption	NPD		System 4		
Thermal resistance	NPD		System 4		
Chemical resistance	NPD		System 4		

Tested system: build up as Sika-ComfortFloor with Sikafloor®-161, Sikafloor®-3000 and Sikafloor®-304 W.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anders Beier Function: General Manager

At Farum on 28 July 2023

Name: Jens Berger Function: Head

Specialized Applicators At Farum on 28 July 2023

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

C€							
15							
	Sika Services AG, Zürich,	Switzerland					
	38327385						
Reaction to fire	Class B _{fl} -s1						
Release of corrosive substances	ase of corrosive substances SR						
Mechanical resistance	Wear resistance	AR0,5					
	Bond strength	B2,0					
	Impact resistance	IR4					
	EN 13813:200	2					
	1611, 0921						
For internal u	ses subject to reaction to fire regulat All other uses — Synthetic res	ions — Synthetic resin screed material in screed material					

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safetyrelated data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

FOR FURTHER INFORMATION:

Sika Danmark A/S Hirsemarken 5 DK-3520 Farum Denmark

Telefon +45 48 18 85 85 www.sika.dk

Declaration of Performance

Sikafloor®-3000 38327385 05/06/2023 3 1008

