

Sikadur®-31 SBA S-04

DECLARATION OF PERFORMANCE

No. 65924380

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	65924380		
2	INTENDED USE/S	EN 1504-4:2004 Structural bonding product for bonded mortar or concrete for use in buildings and civil engineering works		
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich		
4	AUTHORISED REPRESENTATIVE:			
5	SYSTEM/S OF AVCP: System 2+ for type testing System 3 for reaction to fire			
6a	HARMONISED STANDARD:	EN 1504-4:2004		
	Notified body/ies:	0921, 0767		

Sikadur®-31 SBA S-04 65924380 2018.10 , ver. 1 1001

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification	
Bond/adhesion strength Shear adhesion	Pass	System 2+		
	≥ 6 N/mm²	System 2+		
Compressive strength	≥ 30 N/mm ²	System 2+	EN 1504- 4:2004	
Shrinkage/expansion	≤ 0.1 %	System 2+		
/orkability	30 min	System 2+		
Sensitivity to water	Pass	System 2+		
Modulus of elasticity	≥ 2000 N/mm ²	System 2+		
Coefficient of thermal expansion	≤ 100 × 10 ⁻⁶ per K	System 2+		
Glass transition temperature	≥ 40 °C	System 2+	<u>—</u>	
Reaction to fire	Class E	System 3		
Durability	Pass	System 2+		
Dangerous substances	NPD	System 2+		

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anders Beier

Function: General Manager At Farum on 12 November 2019 Name: Lasse Jakobsen

Function: Senior Technical Manager At Farum on 12 November 2019





FULL CE MARKING



1:

Sika Services AG, Zurich, Switzerland

DoP No. 65924380

EN 1504-4:2004

Notified Body 0921, 0767

Structural bonding product for bonded mortar or concrete for use in buildings and civil engineering works

Bond/adhesion strength Pass

Shear adhesion \geq 6 N/mm²

Compressive strength \geq 30 N/mm²

Shrinkage/expansion \leq 0.1 %

Workability 30 min

Sensitivity to water Pass

Modulus of elasticity $\geq 2000 \text{ N/mm}^2$ Coefficient of thermal expansion $\leq 100 \times 10^{-6} \text{ per K}$

Glass transition temperature $\geq 40 \,^{\circ}\text{C}$ Reaction to fire Class E

Durability Pass

http://dop.sika.com



CE MARKING TO BE PLACED ON THE LABEL



12

Sika Services AG, Zurich, Switzerland

DoP No. 65924380

EN 1504-4:2004

Notified Body 0921, 0767

Structural bonding product for bonded mortar or concrete for use in buildings and civil engineering works

Pass, ≥ 6 N/mm², ≥ 30 N/mm², ≤ 0.1 %, 30 min, Pass, ≥ 2000 N/mm², ≤ 100×10^{-6} per K, ≥ 40 °C, Class E, Pass

http://dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.



Sika Danmark A/S

Hirsemarken 5 3520 Farum Denmark www.sika.dk

Declaration of Performance

Sikadur®-31 SBA S-04 65924380 2018.10 , ver. 1 1001

