



EN 1504-2: 2004
 EN 13813

08

1119

DECLARATION OF PERFORMANCE

Sikafloor®-18 Pronto

02	08	01	05	008	0	000004	1131
----	----	----	----	-----	---	--------	------

EN 13813:2002

Declaration of Performance

1. Product Type: Unique identification code of the product-type:	Sikafloor®-
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	18 pronto, batch nr refer to packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	2-part flexible seal coat for internal and external areas based on reactive acrylic resins EN 13813 SR-B1,5-AR1
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikafloor®- Sika Deutschland GmbH Kornwestheimer Strasse 103-107 70439 Stuttgart
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	See 4
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 4
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	



8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	Not relevant (refer to item 7)
--	--------------------------------

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Release of corrosive substances (Synthetic Resin Screed):	SR	EN 13813	EN 13813
Abrasion Resistance:	AR1 ¹⁾	EN 13892-4	
Bond strength:	B 1,5	EN 13892-8	
Impact Resistance:	NPD	EN ISO 6272	
Sound insulation:	NPD	EN ISO 140-1	
Sound absorption:	NPD	EN ISO 354	
Thermal resistance:	NPD	EN 12664	

1) Not broadcast with sand.



EN 1504-2:2004

<p>1. Product Type: Unique identification code of the product-type:</p>	<p>Sikafloor® -</p>
<p>2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):</p>	<p>18 pronto, batch nr refer to packaging</p>
<p>3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:</p>	<p>2-part flexible seal coat for internal and external areas based on reactive acrylic resins</p> <p>Principles 2, 5, 6, 8 of EN 1504-2</p>
<p>4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):</p>	<p>Sikafloor® -</p> <p>Sika Deutschland GmbH Kornwestheimer Strasse 103-107 70439 Stuttgart</p>
<p>5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):</p>	<p>See 4</p>
<p>6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:</p>	<p>System 2+</p>
<p>7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:</p>	<p>1119 Notified factory production control certification body No. 1119 PI performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 1131.</p>

8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Not relevant (refer to item 7)

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Abrasion resistance (Taber test):	< 3000 mg	EN ISO 5470-1	EN 1504-2: 2004
Permeability to CO ₂ :	S _D > 50 m	EN 1062-6	
Permeability to water vapour:	Class III	EN ISO 7783-1	
Capillary absorption and permeability to water:	w < 0.1 kg/(m ² x h ^{0,5})	EN 1062-3	
Resistance to severe chemical attack: ³⁾	Class I	EN 13529	
Impact resistance:	Class I	EN ISO 6272-1	
Adhesion strength by pull-off test:	≥ 2.0 N/mm ²	EN 1542	
Fire Classification:	E _{fl} ¹⁾	EN 13501-1	

¹⁾ Please refer to the Sikafloor® Chemical Resistance Chart.

²⁾ Min. classification, please refer to the individual test certificate.

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:
Sika Denmark A/S translation signed by:



Patrik Horisberger, General Manager



Jimmy Kahl, Head Flooring & Refurbishment

Farum, august 2015

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

For Further Information:
Sika Danmark A/S
Hirsemarken 5
3520 Farum
Denmark

Phone +45 48 18 85 85
www.sika.com

Declaration of Performance Draft 3

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.
