

# Sikafloor®-151

## DECLARATION OF PERFORMANCE

### No. 33500580

|    |  |   |
|----|--|---|
| 1  | <b>UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:</b> | 33500580  |
| 2  | <b>INTENDED USE/S:</b>                                 | Surface protection products – Coating<br>Ingress Protection (1.3)<br>Moisture control (2.2)<br>Physical resistance (5.1)<br>Chemical resistance (6.1)<br>Increasing resistivity (8.2) |
| 3  | <b>MANUFACTURER:</b>                                   | Sika Services AG<br>Tüffenwies 16-22<br>8064 Zürich<br>Switzerland  |
| 4  | <b>AUTHORISED REPRESENTATIVE:</b>                      |   |
| 5  | <b>SYSTEM/S OF AVCP:</b>                               | EN 1504-2: System 2+ (for uses in buildings and civil engineering works)<br><br>EN 1504-2: System 3 (for uses subject to reaction to fire regulations)                                |
| 6a | <b>HARMONISED STANDARD:</b>                            | EN 1504-2:2004  |
|    | Notified body/ies:                                     | 0921<br>1611  |

#### Declaration of Performance

Sikafloor®-151  
33500580  
30.06.2020 , ver. 2  
1008

**7 DECLARED PERFORMANCE/S** Tested systems: Primer Sikafloor®-151 underneath Sikafloor®-264 N (+ 64% quartz sand F34)

| Essential Characteristics                            | Performance                                     | AVCP      | Harmonised Technical Specification |
|--|---|-----------|------------------------------------|
| Linear shrinkage:                                    | NPD   | System 2+ | EN 1504-2:2004                     |
| Compressive strength:                                | NPD   | System 2+ |                                    |
| Coefficient of thermal expansion:                    | NPD   | System 2+ |                                    |
| Abrasion resistance (Taber test) <sup>1)</sup> :     | weight loss < 3000 mg                           | System 2+ |                                    |
| Cross cut:   | NPD   | System 2+ |                                    |
| Permeability to CO <sub>2</sub> :                    | s <sub>d</sub> > 50 m                           | System 2+ |                                    |
| Water vapor permeability:                            | Class II  | System 2+ |                                    |
| Capillary absorption and permeability to water:      | w < 0,1 kg/(m <sup>2</sup> x h <sup>0,5</sup> ) | System 2+ |                                    |
| Thermal compatibility:                               | NPD   | System 2+ |                                    |
| Resistance to thermal shock                          | NPD   | System 2+ |                                    |
| Chemical resistance:                                 | NPD   | System 2+ |                                    |
| Resistance to severe chemical attack <sup>2)</sup> : | Class II  | System 2+ |                                    |
| Crack bridging ability:                              | NPD   | System 2+ |                                    |
| Impact resistance:                                   | Class I   | System 2+ |                                    |
| Adhesion strength by pull off test:                  | ≥ 2,0 (1,5) <sup>3)</sup> N/mm <sup>2</sup>     | System 2+ |                                    |
| Reaction to fire:                                    | B <sub>fi</sub>                                 | System 3  |                                    |
| Skid resistance:                                     | NPD   | System 2+ |                                    |
| Artificial weathering:                               | NPD   | System 2+ |                                    |
| Antistatic behavior:                                 | NPD   | System 2+ |                                    |
| Adhesion on wet concrete:                            | NPD   | System 2+ |                                    |
| Dangerous substances:                                | NPD   | System 2+ |                                    |

<sup>1)</sup> Additionally the requirements according to EN 13813 have to be fulfilled

<sup>2)</sup> Please refer to the Sikafloor Chemical Resistance Chart

<sup>3)</sup> Rigid systems; the value in brackets is the lowest accepted value of any reading.

**Declaration of Performance**

Sikafloor®-151  
33500580  
30.06.2020 , ver. 2  
1008

---

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -  
SPECIFIC TECHNICAL DOCUMENTATION**

---

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

---

Name : Jens Berger  
Function: Target Market  
Manager - Flooring  
Farum, 06.04.2021

Name : Lasse Jakobsen  
Function: Senior  
Technical Manager  
Farum, 06.04.2021



---

End of information as required by Regulation (EU) No 305/2011

**RELATED DECLARATION OF PERFORMANCE**

---

| Product name   | Harmonised standard | DoP number |
|----------------|---------------------|------------|
| Sikafloor®-151 | EN 13813:2002       | 12956378   |

---

**Declaration of Performance**

Sikafloor®-151  
33500580  
30.06.2020 , ver. 2  
1008



19

EN 1504-2:2004

DoP No. 33500580

Sika Services AG, Zürich, Switzerland

Notified Body 0921, 1611

Surface protection products – Coating: Ingress Protection (1.3)  
Moisture control (2.2) Physical resistance (5.1) Chemical resistance (6.1) Increasing resistivity (8.2)

|   |   |
|---|---|
| Abrasion resistance (Taber test):               | weight loss < 3000 mg                           |
| Permeability to CO <sub>2</sub> :               | s <sub>d</sub> > 50 m                           |
| Water vapor permeability:                       | Class II  |
| Capillary absorption and permeability to water: | w < 0,1 kg/(m <sup>2</sup> x h <sup>0,5</sup> ) |
| Resistance to severe chemical attack:           | Class II  |
| Impact resistance:                              | Class I   |
| Adhesion strength by pull off test:             | ≥ 2,0 (1,5)N/mm <sup>2</sup>                    |
| Reaction to fire:                               | B <sub>fl</sub>                                 |

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

## LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Denmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not updated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.


## FOR FURTHER INFORMATION:

Sika Danmark A/S  
Hirsemarken 5  
DK-3520 Farum

Telefon +45 48 18 85 85  
[www.sika.dk](http://www.sika.dk)

## Declaration of Performance

Sikafloor®-151  
33500580  
30.06.2020 , ver. 2  
1008



**Declaration of Performance**

Sikafloor®-151  
33500580  
30.06.2020 , ver. 2  
1008

