Refurbishment
Declaration of Performance
Edition 03/2013
Identification no. 020202010020000021029
Version no. 1

EN 1504-6:2006

EN13813:2002

13

1139

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011 for the product

Sikadur®-12 Pronto

Nr. 0202020100200000021029

EN 13813:2002

Product Type: Unique identification code of the product-type:	Sikadur [®] -12 Pronto
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Batch no.: see packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Synthetic resin screed (systems as per Product Data Sheet) EN 13813 SR – B1,5 – AR0,5 – IR20
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sikadur® Sika Österreich GmbH Bingser Dorfstrasse 23 6700 Bludenz Austria
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	not relevant (see 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 3 for Reaction to fire System 4
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	The notified body No.1140 performed the determination of reaction to fire class on the basis of type testing under system 3 and issued test report: MA39-VFA2008-1539.02
8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:	not relevant



9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Reaction to fire	E(fl)	EN 13501-1	
Release of corrosive substances (Synthetic Resin Screed):	SR	EN 13813	
Water vapour permeability	NPD	EN ISO 7783-2	EN 13813:2002
Compressive strength	NPD	EN 13892-2	
Flexural strength:	NPD	EN 13892-2	
Impact resistance	IR20	EN ISO 6272	
Bond strength	B1.5	EN 13892-8	
Abrasion Resistance:	AR0.5	EN 13892-4	
Sound insulation:	NPD	EN ISO 140-1	
Sound absorption:	NPD	EN ISO 354	
Thermal resistance:	NPD	EN 12664	
Chemical resistance	NPD	EN 13529	

For Further Information Sika Services AG Industriestrasse 26 6060 Sarnen Switzerland

Phone +41 58 436 79 66 Telefax +41 58 436 78 83 www.sika.com

EN 1504-6:2006

Product Type: Unique identification code of the product-type:	Sikadur [®] -12 Pronto
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	Batch no.: see packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification,	2-component ,rapid hardening, flowable construction grout, meeting the requirement of EN1504-6
as foreseen by the manufacturer:	Principle 4 - method 4.2 of EN 1504-9: 2008. Conforming to the Annex ZA Table ZA.1
Name, registered trade name or registered trade mark and contact address of the	Sikadur [®] -
manufacturer as required under Article 11(5):	Sika Österreich GmbH
	Bingser Dorfstrasse 23 6700 Bludenz
	Austria
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	not relevant (see 4)
6. AVCP:	
System or systems of assessment and verification of constancy of performance	System 2+
(AVCP) of the construction product as set out in CPR, Annex V:	System 3 for Reaction to fire
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	Notified factory production control certification body No. 1139 performed the initial inspection of the manufacturing plant and of factory production control under system 2+ and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control (FPC) 1234/08.
	The notified body No.1140 performed the determination of reaction to fire class on the basis of type testing under system 3 and issued test report: MA39-VFA2008-1539.02

Refurbishment
Declaration of Performance
Edition 03/2013
Identification no. 0202020100200000021029
Version no. 1

8. Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has	not relevant (see 7)
been issued:	

9. Declared performance

Pull-out	Displacement ≤ 0.6 mm at load of 75 kN	EN 1881	
Chloride Ion Content	≤ 0.05 %	EN 1015-17	EN 1504-6: 2006
Glass transition temperature	129,4	EN 12614	EN 1304-0. 2000
Creep under tensile load	NPD	prEN 1544	



Refurbishment
Declaration of Performance
Edition 03/2013
Identification no. 0202020100200000021029
Version no. 1

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

ähr Philipp (Product Engineer)

Ing. Retulor igatti (General Manager)

Bludenz, 20th March 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

For further information:

Sika Österreich GmbH Bingser Dorfstrasse 23 6700 Bludenz - Bings Österreich

Phone +43 50 610 Telefax +41 58 610 1901 www.sika.at

