

PRODUCT DATA SHEET

SikaProof® ExTape-100

Self-adhesive tape for external jointing of the SikaProof® A+ waterproofing system

DESCRIPTION

SikaProof® ExTape-100 is a self-adhesive tape based on a butyl adhesive for external jointing and detailing of the SikaProof® A+ membrane system. The tape is composed of a grey aluminium/PET carrier and a divided release liner.

USES

The product is used for:

- Sealing external joints and details within the SikaProof® A+ membrane system.

Please note:

- Do not use the Product in areas where it is permanently exposed to weathering or UV-light.

CHARACTERISTICS / ADVANTAGES

- High adhesion and sealing ability
- Divided release liner for quick and easy installation

PRODUCT INFORMATION

| | |
|------------------------------|--|
| Packaging | 6 rolls packed in one box. Individual roll size: Length 20 m / Width 100 mm Refer to the current price list for available packaging variations. |
| Shelf life | 24 months from date of production |
| Storage conditions | Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between + 5 °C and + 25 °C. Always refer to packaging. Refer to the current price list for available packaging variations. |
| Appearance and colour | Grey carrier coated with black butyl adhesive covered by divided white release liner. |
| Length | 20 m |
| Width | 100 mm |
| Thickness | 1.0 mm |

SYSTEM INFORMATION

| | |
|-------------------------|--|
| System structure | System Components SikaProof® A+ sheet membranes |
|-------------------------|--|

APPLICATION INFORMATION

| | | |
|-------------------------|---------|--------|
| Ambient air temperature | Maximum | +35 °C |
| | Minimum | +5 °C |
| Substrate temperature | Minimum | +5 °C |

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

FURTHER INFORMATION

Refer to the following Sika® Method Statement:
Sika® Method Statement: SikaProof® A+

ECOLOGY, HEALTH AND SAFETY

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

APPLICATION INSTRUCTIONS

IMPORTANT

Strictly follow installation procedures

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

IMPORTANT

Application by trained personnel

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

SUBSTRATE QUALITY

The contact surface is the light yellow SikaProof® membrane side. It must be dry, clean and free of any materials that could impair adhesion.

Application outside of specified application conditions

Note: Under certain circumstances, the Product can be applied in conditions other than the ones specified in this data sheet. However, this requires specific precautions and application methods.

1. Contact Sika technical services for more information.

APPLICATION

IMPORTANT

Exposure to UV or weathering

The Product is not resistant to permanent UV exposure or weathering.

- Protect as soon as possible but not later than 90 days after application
1. Remove the release liner
 2. Apply onto the yellow membrane side
 3. Press firmly using a pressure roller

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S

Hirsemarken 5
3520 Farum
Tlf. +45 48 18 85 85
www.sika.dk



PRODUCT DATA SHEET
SikaProof® ExTape-100
November 2022, Version 01.01
020720308000000019

SikaProofExTape-100-en-DK-(11-2022)-1-1.pdf