

PRODUCT DATA SHEET

Sarnafil® Walkway Pad PVC

Injection moulded PVC Walkway Pad

DESCRIPTION

Sarnafil® Walkway Pad PVC is made of high quality PVC from new Sarnafil® factory waste roofing membrane by injection moulding procedure.

USES

Sarnafil® Walkway Pad PVC is used to provide a durable slip resisting walkway for roof maintenance or access on any Sarnafil® PVC or Sikaplan® PVC roofing system.

FEATURES

- Resistant to permanent UV irradiation
- Outstanding slip resistant surface
- Hot air welding without use of open flames
- Rainwater drainage from beneath the Sarnafil® Walkway Pad PVC is provided by a network of moulded channels
- Recyclable



CERTIFICATES AND TEST REPORTS

- Reaction to fire according to EN 13501-1
- Slip resistance according to BS 7976-2, PTV >50
- Quality management system EN ISO 9001/14001

PRODUCT INFORMATION

Composition	Polyvinyl chloride (PVC)	
Packaging	Cartons with 15 pads	
Appearance and colour	Colour	Dark grey
Shelf life	Sarnafil® Walkway Pad PVC does not expire during correct storage.	
Storage conditions	Sarnafil® Walkway Pad PVC shall be stored in dry conditions.	

Length	600 mm (+3 mm / -3 mm)	
Width	600 mm (+3 mm / -3 mm) without welding tabs	
Thickness	9.3 mm (+0.1 mm / -0.1 mm) including 3 / 5 mm non slip chevron pattern embossing	
Mass per area	2.3 kg/pad	
Surface	Chevron pattern with an alternating rib height of the embossing	
Reaction to fire	Class E	EN 13501-1

APPLICATION INFORMATION

Ambient air temperature	-20 °C min. / +60 °C max.
Substrate temperature	-30 °C min. / +60 °C max.

SYSTEM INFORMATION

System structure	Compatible products:	Sarnafil® G 410 -types Sarnafil® S 327 -types Sikaplan® G / VG / VGWT / S / SG / SGK
-------------------------	----------------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

IMPORTANT CONSIDERATIONS

Geographical / Climate

The use of Sarnafil® Walkway Pad PVC is limited to geographical locations with average monthly minimum temperatures of -50 °C. Permanent ambient temperature during use is limited to +50 °C.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulation is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0.1 % (w/w)

APPLICATION INSTRUCTIONS

APPLICATION

Installation works must be carried out only by Sika instructed contractors for roofing. Installation of some ancillary products, e.g. contact adhesives / cleaners is limited to temperatures above +5 °C. Please observe information given by Product Data Sheets. Special measures may be compulsory for installation below +5 °C ambient temperature due to safety requirements in accordance with national regulations.

APPLICATION METHOD / TOOLS

According to the valid installation instructions for Sarnafil®. Sarnafil® Walkway Pad PVC is installed on site by hot air welding the welding tabs directly onto the Sarnafil® G/S or Sikaplan® PVC membrane.

- Mark a line (e.g. chalk line) in the direction of the installation
- Lay the walkway pads along the marked line
- If arranged in a row, move the pads against the two spacers
- Overlap the welding tabs in the running direction of the welding machine

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.