

## PRODUCT DATA SHEET

# SikaSeal®-632 Fire Putty+

### Fire resistant putty

#### DESCRIPTION

SikaSeal®-632 Fire Putty+ is a fire resistant sealing putty used for small openings around services in fire compartment walls and floors.

#### USES

- Restores the fire resistance performance of a wall or a floor which incorporates small service openings containing cables, insulated and uninsulated metal pipes.
- Suitable for small gaps around services where sealants cannot be applied to the required depth.

#### CHARACTERISTICS / ADVANTAGES

- Up to 4 hours fire resistance
- Easy to apply, hand workable
- Cord is fitted to cover the gap around a service, no need to fill the gap
- Tested for a large variety of relevant wall and floor types

#### APPROVALS / CERTIFICATES

- CE Marking and Declaration of Performance to European Technical Assessment ETA 21/1029, based on EAD 350454-00-1104:2017 - Fire stopping and fire sealing products, penetration seals
- Fire Resistance EN 13501-2, UL-EU, Certificate No.UL-EU-01218-CPR

#### PRODUCT INFORMATION

Composition	Silicone based putty				
Packaging	Please contact our customer service, for information of what packaging sizes are sold in Denmark.				
Appearance and colour	Red cords				
Shelf life	6 years from the date of production				
Storage conditions	The product must be stored in original, unopened and undamaged packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.				
Dimensions	SikaSeal®-632 Fire Putty+ cord dimension: <table border="1"> <tr> <td>Length</td> <td>~200 mm</td> </tr> <tr> <td>Diameter</td> <td>~15 mm</td> </tr> </table>	Length	~200 mm	Diameter	~15 mm
Length	~200 mm				
Diameter	~15 mm				

#### TECHNICAL INFORMATION

Resistance to fire	Refer to 'Approvals / Certificates', Sika digitale håndbog for gennemføringer <a href="https://www.sika.com">Digital håndbog for passiv brandsikring (sika.com)</a> or contact Sika Technical Services for specific information.
--------------------	--

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER INFORMATION

- Sika Application Manual: SikaSeal®-632 Fire Putty+
- Sika digitale håndbog for gennemførelser [Digital håndbog for passiv brandsikring \(sika.com\)](#)

## IMPORTANT CONSIDERATIONS

- SikaSeal®-632 Fire Putty+ may only be used for applications and in combination with products it was tested for.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

The substrate must be clean, dry, sound, free from oils, grease, dust and loose or friable particles.

### APPLICATION METHOD / TOOLS

Reference must be made to the relevant Sika Application Manual or contact Sika Technical Services for additional information.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S  
Hirsemarken 5  
3520 Farum  
Tlf. +45 48 18 85 85  
[www.sika.dk](http://www.sika.dk)



PRODUCT DATA SHEET  
SikaSeal®-632 Fire Putty+  
August 2022, Version 01.01  
020517040000000003

SikaSeal-632FirePutty+-en-DK-(08-2022)-1-1.pdf