

## PRODUCT DATA SHEET

# Sika® Reactivation Primer

### ONE-COMPONENT POLYURETHANE BASED PRIMER

#### DESCRIPTION

Sika® Reactivation Primer is a one-component polyurethane based primer for the reactivation of SikaRoof® MTC, Sikalastic® roofing systems and Sikafloor® balcony waterproofing systems.

#### USES

Primer for use when recoating existing:

- SikaRoof® MTC
- Sikalastic® roofing systems
- Sikafloor® balcony waterproofing systems.

#### CHARACTERISTICS / ADVANTAGES

- One-component - easy and ready to use
- Enhances adhesion to existing Sikalastic® and Sikafloor® systems
- Allows further coats to be safely applied when the standard re-coating window has been exceeded
- Suitable for use over a wide range of existing polyurethane roofing membranes (subject to satisfactory adhesion testing)

#### PRODUCT INFORMATION

<b>Composition</b>	Solvent borne polyurethane	
<b>Packaging</b>	5 l (~5.15 kg) metal container	
<b>Shelf life</b>	12 months from date of production	
<b>Storage conditions</b>	The product must be stored properly in original, unopened and undamaged sealed packaging in dry conditions at temperatures between 0 °C and +25 °C. Higher storage temperatures may reduce shelf life of product. Reference shall also be made to the storage recommendations within the safety data sheet.	
<b>Density</b>	~1.03 kg/l (23 °C)	(EN ISO 2811-1)

#### APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	+5 °C min. / +30 °C max.
<b>Relative Air Humidity</b>	85 % r.h. max.
<b>Substrate Temperature</b>	+5 °C min. / +30 °C max.
<b>Dew Point</b>	Beware of condensation. The substrate and uncured coating must be ≥3 °C above dew point.
<b>Pot Life</b>	Once opened, the product should be used promptly. Storage of partial

containers may result in performance being affected.

Waiting Time / Overcoating	Temperature	Waiting time
	20 °C	3–4 hours
	5 °C	5–6 hours

Sika® Reactivation Primer can be overcoated once cured and tack free. Maximum recoat period within 48 hours of application of the primer. Note: Times are approximate and will be affected by changing ambient conditions, particularly temperature and relative humidity.

## APPLICATION INSTRUCTIONS

### SUBSTRATE PREPARATION

All surfaces to be coated should be thoroughly cleaned by conventional means.

Pre-treat with Sika® Biowash on areas subject to organic growth.

If in doubt apply a test area first.

For detailed information regarding substrate quality/preparation and primer chart please refer to Method Statement.

### APPLICATION

Prepare Sika® Reactivation Primer by stirring thoroughly.

Sika® Reactivation Primer can be applied by short-piled roller or brush.

Allow Sika® Reactivation Primer to dry sufficiently (see table waiting time/overcoating) before overcoating.

### CLEANING OF EQUIPMENT

Clean all tools and application equipment with Thinner C immediately after use. Hardened and/or cured material can only be removed mechanically.

## IMPORTANT CONSIDERATIONS

- Do not apply in wet weather or to wet surfaces.
- Take care to ensure an even coverage and avoid ponding in voids and depressions.
- Do not apply close to the air intake vent of a running air conditioning unit.

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

## ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S

Hirsemarken 5

3520 Farum

Tlf. +45 48 18 85 85

www.sika.dk



PRODUCT DATA SHEET

Sika® Reactivation Primer

May 2020, Version 01.01

02091595100000008

SikaReactivationPrimer-en-DK-(05-2020)-1-1.pdf