

Sikafloor®-3000 Nature

Declaration of Performance No 57903056

1	Unique identification code of the product-type:	57903056
2	Intended use/es:	For internal uses subject to reaction to fire regulations — Synthetic resin screed material All other uses — Synthetic resin screed material
3	Manufacturer:	Sika Services AG Tüffenwies 16 8064 Zürich Switzerland
5	System/s of AVCP:	System 3 (For internal uses subject to reaction to fire regulations) System 4 (All other uses)
6a	Harmonised standard:	EN 13813:2002
	Notified body/ies:	1611

Declaration of Performance

Sikafloor®-3000 Nature

57903056

13/08/2026 1

1041

7 Declared performance/s:			
Essential Characteristics	Performance		AVCP
			Harmonised Technical Specification
Reaction to fire	Class B _{fl} -s1		System 3
Release of corrosive substances	SR		System 4
Water permeability	NPD		System 4
Mechanical resistance	Wear resistance	AR0,5	System 4
	Bond strength	B1,5	
	Impact resistance	≥ IR4	
Sound insulation	NPD		System 4
Sound absorption	NPD		System 4
Thermal resistance	NPD		System 4
Chemical resistance	NPD		System 4

EN 13813:2002

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:	
Name: Tomek Gutowski Function: Corporate Product Certification Manager At Warsaw on 2026-08-13 	Name: Patrycja Młynarska Function: Data Processing Specialist CTD At Warsaw on 2026-08-13 

End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Sikafloor®-3000 Nature

57903056

13/08/2026 1

1041



CE		
19		
Sika Services AG, Zürich, Switzerland		
57903056		
Reaction to fire	Class B _{fi} -s1	
Release of corrosive substances	SR	
Mechanical resistance	Wear resistance	AR0,5
	Bond strength	B1,5
	Impact resistance	≥ IR4
EN 13813:2002		
1611		
For internal uses subject to reaction to fire regulations — Synthetic resin screed material All other uses — Synthetic resin screed material		
http://dop.sika.com		

ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

LEGAL NOTES

Any information provided in this Declaration of Performance ("DoP"), including any descriptions and recommendations relating to the application and end-use of any Sika products ("Products"), are given in good faith based on Sika's current knowledge and experience of the Products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. Please note that the materials, substrates and actual site conditions may vary considerably, and therefore Sika makes no warranty for merchantability or fitness for a particular purpose, and accepts no liability for the application and use of the Products, for any recommendations, or for any advice offered. Prior to using, the Product must be tested for its suitability for the intended application and purpose, and the most recent version of the Product Data Sheet must be consulted. Sika reserves the right to change the properties of its Products any time without prior notice. Any orders for Products or services provided by Sika are subject to Sika's current terms and conditions of sale.

Declaration of Performance

Sikafloor®-3000 Nature

57903056

13/08/2026 1

1041

3 / 3

