

PRODUCT DATA SHEET

Sikafloor®-3000 FX Additive

Lightweight, mineral filler for highly decorative floors with a mineral look

DESCRIPTION

Sikafloor®-3000 FX Additive is a powdered, aluminosilicate additive to Sikafloor®-3000 FX. It is used for achieving a highly decorative, mineral look on elastic floors.

USES

- Sikafloor®-3000 FX Additive is used as a:
- Mineral lightweight filler as an addition to Sikafloor®-3000 FX
 - Filler to achieve a mineral look

Please note:

- The Product may only be used by experienced professionals.
- The Product may only be used for interior applications.

FEATURES

- Free-flowing powder
- Simple to add
- Creates highly decorative floor surfaces with a mineral appearance

CERTIFICATES AND TEST REPORTS

- Indoor Air Comfort Gold EN 16516, eurofins, No. IACG-439-01-05-2022

PRODUCT INFORMATION

Composition	Powdered aluminosilicate
Packaging	Box with 3 bags of 0.4 kg each Refer to the current price list for available packaging variations.
Appearance and colour	Cream-coloured powder
Shelf life	5 years from date of production
Storage conditions	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Protect the Product from direct sunlight. Always refer to packaging. Refer to the current Safety Data Sheet for information on safe handling and storage.
Density	0.65 kg/L

APPLICATION INFORMATION

Mixing ratio	0.4 kg of Sikafloor®-3000 FX Additive per 20.0 kg of Sikafloor®-3000 FX Mixing ratio of Sikafloor®-3000 FX Additive : Sikafloor®-3000 FX = 1 : 50
--------------	--

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

Preconditions

Components A and B of Sikafloor®-3000 FX have been mixed.

1. Add Sikafloor®-3000 FX Additive to the mixed Sikafloor®-3000 FX.
2. Continue to stir until a homogenous mixture has been achieved.

For details on how to apply the Product, see the Sikafloor®-3000 FX Product Data Sheet.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.