



EN 13813

06

DECLARATION OF PERFORMANCE

Sikafloor®-155WN

| | | | | | | | |
|----|----|----|----|-----|---|--------|------|
| 02 | 08 | 01 | 02 | 006 | 0 | 000003 | 1053 |
|----|----|----|----|-----|---|--------|------|

EN 13813:2002

| | |
|--|---|
| 1. Product Type: Unique identification code of the product-type: | Sikafloor®- |
| 2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4): | 155WN, batch nr refer to packaging |
| 3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer: | Two part water dispersed epoxy resin primer used for new concrete, cementitious screeds. hardened concrete existing epoxy floor coatings and epocen levelling layers. EN 13813 SR-B1,5 |
| 4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5): | Sikafloor®- |
| 5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2): | Sikafloor®- Sika S.A.U Crta. Fuencarral, 72 28108 Alcobendas Madrid – España |
| 6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V: | System 4 |
| 7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard: | |

Declaration of Performance



8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Not relevant (refer to item 7)

9. Declared performance

| Essential characteristics | Performance | Test Standard | Harmonised technical specification |
|--|-------------------|---------------|------------------------------------|
| Reaction to fire | NPD ¹⁾ | EN 13501-1 | EN 13813 |
| Release of corrosive substances (Synthetic Resin Screed): | SR | EN 13813 | |
| Water permeability | NPD | EN 1062-3 | |
| Abrasion Resistance: | AR1 ²⁾ | EN 13892-4 | |
| Bond strength: | B 1,5 | EN 13892-8 | |
| Impact Resistance: | NPD | EN ISO 6272 | |
| Sound insulation: | NPD | EN ISO 140-1 | |
| Sound absorption: | NPD | EN ISO 354 | |
| Thermal resistance: | NPD | EN 12664 | |
| Chemical resistance | NPD | EN 13529 | |

1) No Performance determined



10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Julia Gómez Díaz
Technical Department

Ángel González Lucas
General Manager

Alcobendas, February 2013

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

For Further Information:
Sika S.A.U
Crta. Fuencarral, 72
28108 Alcobendas
Madrid

Teléfono +34 91 657 23 75
Fax +34 91 662 19 38
www.sika.com

