
Sikaflex® PRO-3 Purform

DECLARATION OF PERFORMANCE

No. 15886099

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	15886099
2	INTENDED USE/S	EN 14188-2:2004 Cold applied joint sealants intended for use on roads, airfields, bridge decks and parking decks
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 4
6a	HARMONISED STANDARD:	EN 14188-2:2004

Notified body/ies:

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Bonding strength	NPD	System 4	EN 14188-2:2004
Cohesion	NPD	System 4	
Watertightness	NPD	System 4	
Resistance to deformation:			
Elastic recovery	≥ 70 %	System 4	
Loss of volume	≤ 5 %	System 4	
Durability of watertightness against chemicals	≤ 50 %	System 4	
Durability of cohesion against liquid chemicals	Pass, Class A	System 4	
Durability of all mandated characteristics against ageing	Change of tensile modulus at 100 % extension ≤ ±20 %	System 4	
Resistance to flame	NPD	System 4	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION


The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anders Beier
Function: General Manager
At Farum on Dec 13th 2021



Name: Stan Petersen
Function: Head Distribution
At Farum on Dec 13th 2021



End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

Product Name	Harmonised technical specification	DoP Number
Sikaflex® PRO-3 Purform	EN 15651-4:2012	33809346

Declaration of Performance
Sikaflex® PRO-3 Purform
15886099
2020.07 , ver. 1
1003, 1009

Template for translation. Only for
internal use



20

Sika Services AG, Zurich, Switzerland

15886099

EN 14188-2:2004

Cold applied joint sealants intended for use on roads, airfields, bridge decks and parking decks

Resistance to deformation:

Loss of volume	≤5 %
Elastic recovery	≥ 70 %
Durability of watertightness against chemicals	≤ 50 %
Durability of cohesion against liquid chemicals	Pass, Class A
Durability of all mandated characteristics against ageing	Change of tensile modulus at 100 % extension ≤ ±20 %

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance

Sikaflex® PRO-3 Purform
15886099
2020.07 , ver. 1
1003, 1009

Template for translation. Only for
internal use

Sika Danmark A/S
Hirsemarken 5
DK-3520 Farum
Denmark
www.sika.dk

Declaration of Performance
Sikaflex® PRO-3 Purform
15886099
2020.07 , ver. 1
1003, 1009

4/4

Template for translation. Only for
internal use

BUILDING TRUST

