

PRODUCT DATA SHEET

Sika® Antisol®-100

CURING AGENT

DESCRIPTION

Sika® Antisol®-100 is used in concrete construction for curing.

USES

- Concrete for traffic areas e.g. Roads, airfields
- For non-traffic components
- Screed
- At high temperatures, strong sunlight, wind movement as well as in low humidity

FEATURES

Sika® Antisol®-100 is a highly effective solvent-free wax emulsion and creates, a largely water vapour impermeable protective film on the concrete surface after drying.

- Blocking the surface pores of the concrete
- Extremely high evaporation protection
- Protection against dehydration
- Prevention against contraction and shrinkage cracks

PRODUCT INFORMATION

Composition	Paraffin wax
Packaging	Canister: 20 kg Drum: 190 kg Container: 900 kg
Appearance and colour	Fluid / White
Shelf life	6 months shelf life after production date
Storage conditions	In sealed container protected against frost, strong sunlight and contamination.
Density	0.99 g/cm³ at +20°C
Solubility	in water

Sika® Antisol®-100October 2024, Version 01.01
021405031000000174

APPLICATION INFORMATION

Recommended dosage	150 g/m² to 200 g/m²
Ambient air temperature	>+1°C

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/SHirsemarken 5
3520 Farum

Tlf. +45 48 18 85 85 www.sika.dk





PRODUCT DATA SHEET Sika® Antisol®-100October 2024, Version 01.01
021405031000000174



SikaAntisol-100-en-DK-(10-2024)-1-1.pdf