
Sikadur[®]-52 Injection Normal

DECLARATION OF PERFORMANCE

No. 36748706

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	36748706
2	INTENDED USE/S	EN 1504-5:2004 Construction products: Concrete injection for force transmitting filling of cracks, voids and interstices (F). Intended use: In buildings and civil engineering works. U(F1)W(3)(1)(8/30)(0)
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+
6a	HARMONISED STANDARD:	EN 1504-5:2004
	Notified body/ies:	0921

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Adhesion by tensile bond strength	Cohesive failure in the substrate	System 2+	EN 1504-5:2004
Adhesion by slant shear strength	NPD	System 2+	
Shrinkage: Volumetric shrinkage	NPD	System 2+	
Glass transition temperature	> 40 °C	System 2+	
Workability: Injectability into dry medium	0.3 mm	System 2+	
Workability: Injectability into non dry medium	0.3 mm	System 2+	
Chloride content	NPD	System 2+	
Durability	Cohesive failure in the substrate	System 2+	
Corrosion behavior	Deemed to have no corrosive effect	System 2+	
Release of dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Anders Beier
General Manager
At Farum on 04 November 2019

Lasse Jakobsen
Senior Technical Manager
At Farum on 04 November 2019

End of information as required by Regulation (EU) No 305/2011



17

Sika Services AG, Zurich, Switzerland

36748706

EN 1504-5:2004

Notified Body 0921

Construction products: Concrete injection for force transmitting filling of cracks, voids and interstices (F).
Intended use: In buildings and civil engineering works.
U(F1)W(3)(1)(8/30)(0)

Adhesion by tensile bond strength	Cohesive failure in the substrate
Glass transition temperature	> 40 °C
Workability: Injectability into dry medium	0.3 mm
Workability: Injectability into non dry medium	0.3 mm
Durability	Cohesive failure in the substrate
Corrosion behavior	Deemed to have no corrosive effect

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

"Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the echnological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Denmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise."

Declaration of Performance

Sikadur®-52 Injection Normal
84588089
2019.10, ver. 2
1001

3/4

BUILDING TRUST



Sika Danmark A/S
Hirsemarken 5
3520 Farum
Denmark
www.sika.dk

Declaration of Performance
Sikadur®-52 Injection Normal
84588089
2019.10, ver. 2
1001

4/4

BUILDING TRUST

