

SikaGrout®-312

DECLARATION OF PERFORMANCE 13886990

1	UNIQUE IDENTIFICATION CODE OF PRODUCT TYPE:	13886990
2	INTENDED USE/S	Anchoring Product (based on hydraulic cement) Method 4.2
3	MANUFACTURER:	Sika Österreich GmbH Bingser Dorfstraße 23 A-6700 Bludenz
4	AUTHORIZED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	2+ 3 (Reaction to fire)
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body:	1139

Declaration of performance

SikaGrout®-312
13886990
2017.10 , Vers. 01
1029

7 DECLARED PERFORMANCE/S:

Essential Characteristics	Performance	Harmonised Technical Specification
Pull out strength displacement	≤ 0.6 mm at load of 75 kN	EN 1504-6:2006
Chloride ion content	≤ 0.05 %	
Glass transition temperature	NPD	
Creep under tensile load	NPD	
Dangerous substances	See local safety data sheet	
Reaction to fire	Class A1	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier
Function: Managing director
Farum, August 25th 2020



Name : Jens Berger
Function: Target Market Manager
Flooring & Engineered Refurbishment
Farum, August 25th 2020



End of information as required by Regulation (EU) No. 305/2011

DECLARATION OF PERFORMANCE

SikaGrout®-312
13886990
2017.10, Vers 01
1029





17

Sika Österreich GmbH, Bingser Dorfstraße 23, A-6700 Bludenz

DoP No. 13886990

EN 1504-6:2006

Notified body 1139

Anchoring Product
(based on hydraulic cement)
method 4.2

Pull out strength displacement	≤ 0.6 mm at load of 75 kN
Chloride ion content	≤ 0.05 %
Dangerous substances	See local safety data sheet
Reaction to fire	Class A1

dop.sika.com

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data, copies of which can be found under www.sika.at.

LEGAL NOTE

"Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise."

DECLARATION OF PERFORMANCE

SikaGrout®-312
13886990
2017.10, Vers 01
1029

3/4

BUILDING TRUST



SIKA DANMARK A/S
Hirsemarken 5
DK-3520 Farum
Denmark

DECLARATION OF PERFORMANCE
SikaGrout®-312
13886990
2017.10, Vers 01
1029

4/4

BUILDING TRUST

