

Sikadur[®]-32+

DECLARATION OF PERFORMANCE

No. 85644331

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	85644331
2	INTENDED USE/S	EN 1504-6:2006 Anchoring products for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-6:2006
	Notified body/ies:	0099, 0370

7 DECLARED PERFORMANCE/S


Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Pull-out strength	Displacement $\leq 0,6$ mm at load of 75 kN	System 2+	EN 1504-6:2006
Chloride ion content	≤ 0.05 %	System 2+	
Glass transition temperature	≥ 45 °C	System 2+	
Reaction to fire	Class B _{FL} -s1 / C-s1, d0	System 3	
Durability/Creep under tensile load	$\leq 0,6$ mm at 50 kN for 3 months	System 2+	
Dangerous substances	NPD	System 2+	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier
Function: General Manager
Farum 20 July 2023



Name : Lasse Jakobsen
Function: Senior Technical Manager
Farum 20 July 2023



End of information as required by Regulation (EU) No 305/2011



21

Sika Services AG, Zurich, Switzerland

85644331

EN 1504-6:2006

Notified Body 0099, 0370

Anchoring products for strengthening concrete by installing reinforcing steel (rebars) for use in buildings and civil engineering works

Pull-out strength	Displacement \leq 0,6 mm at load of 75 kN
Chloride ion content	\leq 0.05 %
Glass transition temperature	\geq 45 °C
Reaction to fire	Class B _{FL} -s1 / C-s1, d0
Durability/Creep under tensile load	\leq 0,6 mm at 50 kN for 3 months

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance

Sikadur®-32+
85644331
2021.03 , ver. 1
1053

Template for translation. Only for
internal use

Sika)
=
) M 7
)
www.sika.

Declaration of Performance

Sikadur®-32+
85644331
2021.03 , ver. 1
1053

Template for translation. Only for
internal use

