

# EC-TYPE EXAMINATION CERTIFICATE (MODULE B)

Certificate No:  
**MEDB000019T**  
Revision No:  
**2**

Application of: Directive 2014/90/EU of 23 July 2014 on marine equipment (MED). This Certificate is issued by DNV SE based on the notification of the Federal Maritime and Hydrographic Agency of Germany.

## This is to certify:

**That the Surface materials and floor coverings with low flame-spread characteristics: decorative veneers**

with type designation(s)  
**SikaFlex®-591**

Issued to  
**Sika Services AG**  
**Zürich, ZH, Switzerland**

is found to comply with the requirements in the following Regulations/Standards:  
Regulation (EU) 2020/1170,  
item No. MED/3.18a. SOLAS 74, Reg. II-2/3, II-2/5, II-2/6 & X/3, IMO MSC/Circ. 1120, 2000 HSC Code 7 and IMO 2010 FTP Code


Further details of the equipment and conditions for certification are given overleaf.

This Certificate is valid until **2026-08-08**.

Issued at **Hamburg** on **2021-08-09**

DNV local station:  
**Augsburg**

Approval Engineer:  
**Timo Linn**



Notified Body  
No.: **0098**

for DNV SE

**Christine Mydlak-Roeder**  
**Head of Notified Body**

A U.S. Coast Guard approval number will be assigned to the equipment when the production module has been completed and will appear on the production module certificate (module D, E or F) of Annex B of the MED is fully complied with and controlled by a written inspection agreement with a Notified Body. The product liability rests with the manufacturer or his representative in accordance with Directive 2014/90/EU.

This certificate is valid for equipment, which is conform to the approved type. The manufacturer shall inform DNV SE of any changes to the approved equipment. This certificate remains valid unless suspended, withdrawn, recalled or cancelled. Should the specified regulations or standards be amended during the validity of this certificate, the product is to be re-approved before being placed on board a vessel to which the amended regulations or standards apply.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



## Product description

**SikaFlex®-591** is an elastic PUR-Hybrid sealant based on a silane terminated polymer.

Applied maximum amount	200 g/m <sup>2</sup>
Organic content	45%
Colour	Black / White
Max. thickness	0.2 mm
Nominal density	1.5 kg/l

## Application/Limitation

Approved for use as low flame spread surface material, not generating excessive quantities of smoke nor toxic products in fire.

Approved Color: all color variations

Approved for use as decorative veneers on non-combustible substrate with a greater thickness than 15 mm.

Any adhesive used, other than the one used during testing, has to be tested for low flame spread characteristics according to IMO 2010 FTP Code part 5 and to be approved according to the Marine Equipment Directive and bear the Mark of Conformity.

The product satisfies the requirement for maximum calorific value (ref. SOLAS Chapter II-2, Reg 5.3.2.2) without further testing.

Each product is to be supplied with its instructions for installation, use and maintenance.

## Type Examination documentation

Test Report No. 5P08556rev1 dated 2018-01-24 issued by SP Technical Research Institute of Sweden.

Test Report No. 8P01619-1 dated 2018-03-15 issued by SP Technical Research Institute of Sweden.

Manufacturers's product data sheet SikaFlex®-591 Version 1 (01/16)

## Tests carried out

Tested according to IMO Res. MSC.307(88) – 2010 FTP Code Annex 1, Part 5 and in compliance with Annex 2, Item 2.2 and 2.3.

## Marking of product

The product or packing is to be marked with:

- name and address of manufacturer,
- type designation,
- fire technical rating and
- the MED Mark of Conformity (see page 1) and USCG approval number, if applicable.