

PRODUCT DATA SHEET

SikaProof® Tape A+

SELF-ADHESIVE TAPE FOR EXTERNAL JOINTING OF SIKAPROOF A+ WATERPROOFING SYSTEM

DESCRIPTION

SikaProof® Tape A+ is a self-adhesive tape based on a polyacrylate adhesive with a carrier film and a release liner.

USES

SikaProof® Tape A+ may only be used by experienced professionals.

- Sealing and bonding overlap joints, connections and details within the SikaProof® A+ membrane system.

CHARACTERISTICS / ADVANTAGES

- Fully bonded to the concrete structure
- No lateral water migration (identical to SikaProof® A+ membrane)
- High adhesion and sealing capability, especially in cold and damp conditions
- Simple and fast to install

PRODUCT INFORMATION

Packaging	2 rolls packed in one cardboard box	
	Individual roll size	Length 25 m Width 150 mm
Appearance / Colour	Top layer	Grey hybrid bonding layer with yellow waterproofing layer
	Bottom layer	Transparent polyacrylate adhesive covered with a white release liner
Shelf life	18 months from date of production	
Storage conditions	Product must be stored in original unopened and undamaged sealed packaging in dry conditions and temperatures between +5 °C and +30 °C. Always refer to packaging.	
Thickness	1,80 mm	

SYSTEMS

System Structure	SikaProof® Tape A+ is a system component for internal jointing of the SikaProof® A+ membrane system. For more detailed information, refer to Sika® Method Statement: SikaProof® A+ system
-------------------------	---

APPLICATION INFORMATION

Ambient Air Temperature +5 °C min. / +40 °C max.

Substrate Temperature +5°C min.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

The contact surface is the grey SikaProof® A+ hybrid bonding layer. It must be dry (or slightly damp), clean and free of any materials that could impair the adhesion. If the substrate requirements are not achieved, suitable measures must be taken. Contact Sika® Technical Services for more information.

APPLICATION METHOD / TOOLS

Reference must be made to further documentation where applicable, such as relevant method statement, application manual and installation or working instructions.

Remove the release liner, apply onto the grey SikaProof® A+ membrane side and press tape firmly using a pressure roller.

FURTHER INFORMATION

- Sika® Method Statement: SikaProof® A+ system

IMPORTANT CONSIDERATIONS

Installation work must only be carried out by Sika® trained, approved or competent contractors experienced in this type of application.

- Do not install SikaProof® Tape A+ during continuous or prolonged rain or snowfall.
- The substrate quality and conditions must be fulfilled or appropriate measures must be taken. Contact Sika® Technical Services for more information.
- SikaProof® Tape A+ is not permanently UV resistant.
- The structural concrete must be placed within 90 days after the SikaProof® A+ membrane system is installed.

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for the exact product data and uses.

ECOLOGY, HEALTH AND SAFETY

REGULATION (EC) NO 1907/2006 - REACH

This product is an article as defined in article 3 of regulation (EC) No 1907/2006 (REACH). It contains no substances which are intended to be released from the article under normal or reasonably foreseeable conditions of use. A safety data sheet following article 31 of the same regulations is not needed to bring the product to the market, to transport or to use it. For safe use follow the instructions given in this product data sheet. Based on our current knowledge, this product does not contain SVHC (substances of very high concern) as listed in Annex XIV of the REACH regulation or on the candidate list published by the European Chemicals Agency in concentrations above 0,1% (w/w).

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.