

Sikafloor[®]-376

DECLARATION OF PERFORMANCE

No. 79931933

| | | |
|-----------|--|--|
| 1 | UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE: | 79931933 |
| 2 | INTENDED USE/S | EN 1504-2:2004 Surface protection products – Coating Ingress protection (1.3) Moisture control (2.2) Physical resistance (5.1) Chemical resistance (6.1) Increasing resistivity (8.2) |
| 3 | MANUFACTURER: | Sika Deutschland GmbH Kornwestheimer Str. 103 - 107 70439 Stuttgart |
| 4 | AUTHORISED REPRESENTATIVE: | |
| 5 | SYSTEM/S OF AVCP: | System 2+ (for uses in buildings and civil engineering works) System 3 (for uses subject to reaction to fire regulations) |
| 6a | HARMONISED STANDARD: | EN 1504-2:2004 |
| | Notified body/ies: | 0921 1508 |

Declaration of Performance

Sikafloor[®]-376
79931933
08.02.2018 , ver. 1
1008

7 DECLARED PERFORMANCE/S Tested system: Sikafloor®-161 (broadcasted with quartz sand 0.3-0.8mm), Sikafloor®-376, Sikafloor®-377 (+ 40% quartz sand 0.1-0.3mm and broadcasted with quartz sand 0.3-0.8mm) and Sikafloor®-378

| Essential Characteristics | Performance | AVCP | Harmonised Technical Specification |
|--|---|-----------|------------------------------------|
| Linear shrinkage: | NPD | System 2+ | |
| Compressive strength: | NPD | System 2+ | |
| Coefficient of thermal expansion: | NPD | System 2+ | |
| Abrasion resistance (Taber test) ¹⁾ : | weight loss < 3000 mg | System 2+ | |
| Cross cut: | NPD | System 2+ | |
| Permeability to CO ₂ : | s _D > 50 m | System 2+ | |
| Water vapor permeability: | Class III | System 2+ | |
| Capillary absorption and permeability to water: | w < 0,1 kg/(m ² x h ^{0,5}) | System 2+ | |
| Thermal compatibility: | NPD | System 2+ | |
| Resistance to thermal shock | NPD | System 2+ | |
| Chemical resistance: | NPD | System 2+ | EN 1504-2:2004 |
| Resistance to severe chemical attack ²⁾ : | Class I | System 2+ | |
| Crack bridging ability: | NPD | System 2+ | |
| Impact resistance: | Class I | System 2+ | |
| Adhesion strength by pull off test: | ≥ 2,0 (1,5) ³⁾ N/mm ² | System 2+ | |
| Reaction to fire: | B _{fl} | System 3 | |
| Skid resistance: | NPD | System 2+ | |
| Artificial weathering: | NPD | System 2+ | |
| Antistatic behavior: | NPD | System 2+ | |
| Adhesion on wet concrete: | NPD | System 2+ | |
| Dangerous substances: | NPD | System 2+ | |

¹⁾ Additionally the requirements according to EN 13813 have to be fulfilled

²⁾ Please refer to the Sikafloor Chemical Resistance Chart

³⁾ The value in brackets is the lowest accepted value of any reading.

Declaration of Performance

Sikafloor®-376

79931933

08.02.2018 , ver.1

1008

**8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR -
SPECIFIC TECHNICAL DOCUMENTATION**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier
Function: General Manager
At Farum on 12 November 2019

Name : Lasse Jakobsen
Function: Senior Technical Manager
At Farum on 12 November 2019



.....



.....

End of information as required by Regulation (EU) No 305/2011

RELATED DECLARATION OF PERFORMANCE

| Product name | Harmonised standard | DoP number |
|---------------------|----------------------------|-------------------|
| Sikafloor®-376 | EN 13813: 2002 | 44518288 |

Declaration of Performance

Sikafloor®-376
79931933
08.02.2018 , ver.1
1008



17

EN 1504-2:2004

DoP No. 79931933

Sika Deutschland GmbH, Stuttgart

Notified Body 0921, 1508

Surface protection products – Coating: Ingress protection (1.3)
Moisture control (2.2) Physical resistance (5.1) Chemical resistance (6.1) Increasing resistivity (8.2)

| | |
|---|------------------------------------|
| Abrasion resistance (Taber test): | weight loss < 3000 mg |
| Permeability to CO ₂ : | s _D > 50 m |
| Water vapor permeability: | Class III |
| Capillary absorption and permeability to water: | w < 0,1 kg/(m ² x h0,5) |
| Resistance to severe chemical attack: | Class I |
| Impact resistance: | Class I |
| Adhesion strength by pull off test: | ≥ 2,0 (1,5)N/mm ² |
| Reaction to fire: | B _{fl} |

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Declaration of Performance

Sikafloor®-376

79931933

08.02.2018 , ver.1

1008

4/5

BUILDING TRUST




LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or endusers of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

FOR FURTHER INFORMATION:

Sika Danmark A/S
Hirsemarken 5
3520 Farum

48 18 85 85
www.sika.dk



Declaration of Performance

Sikafloor®-376
79931933
08.02.2018 , ver.1
1008