

PRODUCT DATA SHEET

SikaInject® AC-20 DE

Formerly TPH.® PUR-O-STOP FS-C / multi-product catalyst for polyurethane resins

DESCRIPTION

SikaInject® AC-20 DE is an accelerator for various Sika Injection Resins based on polyurethane, such as: SikaInject®-201 DE, SikaInject®-210 DE, SikaInject®-216 DE, further on request

USES

SikaInject® AC-20 DE may only be used by experienced professionals.

Accelerates the base resin where short potlife is needed, e.g.

- in flowing water applications
- in cold season
- in cold water applications

FEATURES

Only one accelerator for various SikaInject®-PU

- Shortens potlife
- Increase of efficiency
- Reduction of product loss, e.g. in flowing water

CERTIFICATES AND TEST REPORTS

German General Building Inspectorate Approval for curtain grouting, AbZ, DIBT Berlin

PRODUCT INFORMATION

Packaging	4.5 kg / larger packaging on request
Colour	colorless, liquid
Shelf life	12 months from date of production
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperature between +15 °C and +25 °C.
Density	~ 1.03 kg/l (DIN EN ISO 2811-1)
Viscosity	~ 120 mPas (DIN EN ISO 2555)

APPLICATION INFORMATION

Mixing ratio	Measure and add small quantities of SikaInject®-AC 20 DE into part A of the respective SikaInject®-PU Injection Resin and mix homogeneously (no streaks). The exact quantity (potlife table) can be found in the Product Data Sheet of the referring injection resin.
--------------	---

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheets (SDS) containing physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the declared data for this product may vary from country to country. Please consult the local Product Data Sheet for the exact product data.

LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Sika Danmark A/S

Hirsemarken 5
3520 Farum
Tlf. +45 48 18 85 85
www.sika.dk



PRODUCT DATA SHEET

SikaInject® AC-20 DE
October 2026, Version 01.01
020707010020000057

SikaInjectAC-20DE-en-DK-(10-2026)-1-1.pdf