

Sika MonoTop[®]-412 NFG

DECLARATION OF PERFORMANCE

No. 25689022

1	UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:	25689022
2	INTENDED USE/S	EN 1504-3:2005 Structural and non-structural repair products for concrete for application in buildings and civil engineering work
3	MANUFACTURER:	Sika Services AG Tüffenwies 16-22 8064 Zürich
4	AUTHORISED REPRESENTATIVE:	
5	SYSTEM/S OF AVCP:	System 2+ for type testing System 3 for reaction to fire
6a	HARMONISED STANDARD:	EN 1504-3:2005
	Notified body/ies:	1139

Declaration of Performance

Sika MonoTop[®]-412 NFG
25689022
2017.11, ver. 001
1029

7 DECLARED PERFORMANCE/S

Essential Characteristics	Performance	Harmonised Technical Specification
Compression strength	≥ 45 Mpa	EN 1504-3:2005
Chloride ion content	≤ 0.05 %	
Adhesive bond	≥ 2.0 MPa	
Carbonation resistance	Passes	
Elastic modulus	≥ 20 GPa	
Thermal compatibility freeze-thaw	≥ 2.0 MPa	
Skid resistance	NPD	
Coefficient of thermal expansion	NPD	
Capillary absorption	≤ 0.5 kg.m ⁻² .h ^{-0.5}	
Reaction to fire	Class A1	
Release of dangerous substances	NPD	

8 APPROPRIATE TECHNICAL DOCUMENTATION AND/OR - SPECIFIC TECHNICAL DOCUMENTATION

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name : Anders Beier
Function: General Manager
At Farum on 21 May 2019



Name : Heine Sønnichsen
Function: Head Flooring & Refurbishment
At Farum on 21 May 2019



End of information as required by Regulation (EU) No 305/2011

Declaration of Performance

Sika MonoTop®-412 NFG
25689022
2017.11 , ver. 001
1029



13

DoP No. 25689022

Sika Services AG, Zurich, Switzerland

EN 1504-3:2005

Notified Body 1139

Structural and non-structural repair products for concrete
for application in buildings and civil engineering work

Compression strength	≥ 45 Mpa
Chloride ion content	≤ 0.05 %
Adhesive bond	≥ 2.0 MPa
Carbonation resistance	Passes
Elastic modulus	≥ 20 GPa
Thermal compatibility freeze-thaw	≥ 2.0 MPa
Capillary absorption	≤ 0.5 kg.m ⁻² .h ^{-0.5}
Reaction to fire	Class A1

<http://dop.sika.com>

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTE

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

Declaration of Performance

Sika MonoTop®-412 NFG
25689022
2017.11 , ver. 001
1029

Sika Danmark A/S
Hirsemarken 5
DK-3520 Farum
Denmark
www.sika.dk

Declaration of Performance

Sika MonoTop®-412 NFG
25689022
2017.11 , ver. 001
1029

