



EN 13963
 EN 15824

11
 12

0402

DECLARATION OF PERFORMANCE

Sika® Filler-110

01	03	04	02	001	0	000013	1084
----	----	----	----	-----	---	--------	------

Declaration of Performance

1. Product Type: Unique identification code of the product-type:	Sika® Filler
2. Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):	-110, batch nr refer to packaging
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	Waterborne multipurpose fine surface sand filler. Indoor fine spackling of concrete, gypsum, fabric, wallpaper etc.
4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):	Sika® Filler Sika Denmark A/S Præstemosevej 2-4 DK-3480 Fredensborg
5. Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):	Not relevant (refer to item 4)
6. AVCP: System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V:	System 4
7. Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:	0402 Notified test body 0402 issued under AVCP system 4 tests to EN 13963: fire tests According To EN13823 (SBI method) test report no. P602832 Reaction to fire classification report of product "joint filler 5%" test report no. P602832A. Heat of combustion According To EN ISO 1716. Test reports P602832-01A Rev., P602832-01B/rev and F622673. 0402 Notified test body 0402 issued under AVCP system 4 tests to EN 15824: Fire test according To EN 13823, 2002 (SBI method) and ignitability according To EN ISO 11925-2. Test report Nr.PX05926, PX18221rev2



8. Notified body (ETA):

In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued:

Not relevant (refer to item 7)

9. Declared performance

Essential characteristics	Performance	Test Standard	Harmonised technical specification
Bending Tensile strength	>320 N	EN 13963	EN 13963
Reaction to fire:	A2-s 1,d0	EN 13501-1	
Adhesion	>0,3 MPa	EN 1542	EN 15824
Reaction to fire:	B-s 1,d0	EN 13501-1	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:



Jimmy Kahl

Product engineer



Patrik Horisberger

General Manager

20 December 2013, Fredensborg

Ecology, Health and Safety Information (REACH)

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

Legal note:

This information is given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



For further Information:
Sika Danmark A/S
Præstemosevej 2-4
DK-3480 Fredensborg
Danmark

Phone. +45 48 18 85 85
Telefax +45 48 18 84 96
www.sika.com