

# Sikafloor®-2510 W

## Declaration of Performance No 99375950

1	Unique identification code of the product-type:	99375950
2	Intended use/es:	<p>For uses in buildings and civil engineering works: moisture control (2.2), increasing resistivity (8.2) — Surface protection products — coating</p> <p>For uses in buildings and civil engineering works: physical resistance (5.1) — Surface protection products — coating</p> <p>For uses in buildings and civil engineering works: ingress protection (1.3) — Surface protection products — coating</p> <p>For uses in buildings and civil engineering works: chemical resistance (6.1) — Surface protection products — coating</p> <p>For uses subject to reaction to fire regulations — Surface protection products — coating</p>
3	Manufacturer:	<p>Sika Services AG</p> <p>Tüffenwies 16</p> <p>8064 Zürich</p> <p>Switzerland</p>
5	System/s of AVCP:	<p>System 2+ (For uses in buildings and civil engineering works: moisture control (2.2), increasing resistivity (8.2))</p> <p>System 2+ (For uses in buildings and civil engineering works: physical resistance (5.1))</p> <p>System 2+ (For uses in buildings and civil engineering works: ingress protection (1.3))</p> <p>System 2+ (For uses in buildings and civil engineering works: chemical resistance (6.1))</p> <p>System 3 (For uses subject to reaction to fire regulations)</p>
6a	Harmonised standard:	EN 1504-2:2004
	Notified body/ies:	0921, 1611

### Declaration of Performance

Sikafloor®-2510 W

99375950

09/01/2024 2

1008

1 / 3


7 Declared performance/s:

Essential Characteristics	Performance	AVCP	Harmonised Technical Specification
Linear shrinkage	NPD	System 2+	EN 1504-2:2004
Compressive strength	NPD	System 2+	
Coefficient of thermal expansion	NPD	System 2+	
Abrasion resistance	< 3000 mg (H22 / 1000 cycles / 1000 g)	System 2+	
Cross cut	NPD	System 2+	
Permeability to CO2	$s_D > 50 \text{ m}$	System 2+	
Water vapour permeability	Class II: $5 \text{ m} \leq S_D \leq 50 \text{ m}$	System 2+	
Capillary absorption and permeability to water	$w < 0.1 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0.5}$	System 2+	
Thermal compatibility	NPD	System 2+	
Resistance to thermal shock	NPD	System 2+	
Chemical resistance	NPD	System 2+	
Resistance to severe chemical attack	< 50 % (Class II: 28 d without pressure)	System 2+	
Crack bridging ability	NPD	System 2+	
Impact resistance	Class I: $\geq 4 \text{ Nm}$	System 2+	
Adhesion strength by pull off test	$\geq 2.0 (1.5) \text{ N/mm}^2$	System 2+	
Reaction to fire	Class B <sub>f</sub> -s1	System 3	
Skid resistance	NPD	System 2+	
Artificial weathering	NPD	System 2+	
Antistatic behaviour	NPD	System 2+	
Adhesion on wet concrete	NPD	System 2+	
Dangerous substances	NPD	System 2+	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: Anders Beier  
Function: General Manager  
At Farum on 26 February 2024



Name: Jens Berger  
Function: Head Specialized Applicators  
At Farum on 26 February 2024



End of information as required by Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance

Declaration of Performance

Sikafloor®-2510 W

99375950

09/01/2024 2

1008



Abrasion resistance	< 3000 mg (H22 / 1000 cycles / 1000 g)
---------------------	--

Permeability to CO <sub>2</sub>	$s_D > 50 \text{ m}$
---------------------------------	----------------------

Water vapour permeability	Class II: $5 \text{ m} \leq s_D \leq 50 \text{ m}$
---------------------------	--

Capillary absorption and permeability to water	$w < 0.1 \text{ kg} \cdot \text{m}^{-2} \cdot \text{h}^{-0.5}$
--	--

Resistance to severe chemical attack	< 50 % (Class II: 28 d without pressure)
--------------------------------------	--

Impact resistance	Class I: $\geq 4 \text{ Nm}$
-------------------	------------------------------

Adhesion strength by pull off test	$\geq 2.0 \text{ (1.5) N/mm}^2$
------------------------------------	---------------------------------

Reaction to fire	Class B <sub>fi</sub> -s1
------------------	---------------------------

EN 1504-2:2004

0921, 1611

For uses in buildings and civil engineering works: moisture control (2.2), increasing resistivity (8.2) — Surface protection products — coating

For uses in buildings and civil engineering works: physical resistance (5.1) — Surface protection products — coating

For uses in buildings and civil engineering works: ingress protection (1.3) — Surface protection products — coating

For uses in buildings and civil engineering works: chemical resistance (6.1) — Surface protection products — coating

For uses subject to reaction to fire regulations — Surface protection products — coating

<http://dop.sika.com>

## ECOLOGY, HEALTH AND SAFETY (REACH)

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

## LEGAL NOTES

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product have been given in good faith based on our own experiences and based of approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is effected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

## FOR FURTHER INFORMATION:

Sika Danmark A/S  
Hirsemarken 5  
DK-3520 Farum  
Denmark

Telefon +45 48 18 85 85  
[www.sika.dk](http://www.sika.dk)

## Declaration of Performance

Sikafloor®-2510 W

99375950

09/01/2024 2

1008

3 / 3