

## PRODUCT DATA SHEET

# Sika® Tooling Agent N

Tooling agent to create smooth finishes with Sikaflex® sealants

**TYPICAL PRODUCT DATA (FURTHER VALUES SEE SAFETY DATA SHEET)**

<b>Chemical base</b>	Aqueous tenside solution
<b>Color (CQP001-1)</b>	Colorless transparent
<b>Application temperature</b>	5 – 35 °C
<b>Shelf life</b>	12 months <sup>A</sup>

CQP = Corporate Quality Procedure

<sup>A)</sup> stored in sealed container in a dry place between 5 and 25 °C

**DESCRIPTION**

Sika® Tooling Agent N is a water-based, solvent-free tooling agent for Sika's elastic sealants and adhesives.

**PRODUCT BENEFITS**

- pH neutral
- Compatible with common surfaces
- No washing-out or etching of fresh applied sealants or adhesives

**AREAS OF APPLICATION**

Sika® Tooling Agent N is designed for smoothening freshly applied Sika elastic sealants and adhesives. In tested cases, Sika® Tooling Agent N did not affect paint finishes and further commonly used surfaces. However, in critical cases it is recommend to check compatibility by tests, especially with fresh and/or water-based paints.

This product is suitable for experienced professional users only. Tests with actual substrates and conditions have to be performed ensuring material compatibility.

## METHOD OF APPLICATION

Sika® Tooling Agent N may be sprayed directly on the surface and tooled with a smoothing tool. Another type of application is to smooth the surface with a tool previously immersed in Sika® Tooling Agent N. The viscosity of Sika® Tooling Agent N can be adjusted by adding clean water to the product. Tightly re-seal container immediately after each use.

## Storage condition

Unopened containers may be stored between 5 °C and 25 °C.

Opened containers must be used within a few weeks. Degradation of the product will result in growth of micro-organisms and a subsequent unpleasant odor. In such cases, the product is to be disposed of.

## IMPORTANT NOTE

Sika® Tooling Agent N contains a small amount of water soluble polymers which remain on the surface. If the smoothed product needs to be overpainted, remove the above mentioned polymers by rinsing the surface with clean water.

## FURTHER INFORMATION

The information herein is offered for general guidance only. Advice on specific applications is available on request from the Technical Department of Sika Industry.

Copies of the following publications are available on request:

- Safety Data Sheets

## PACKAGING INFORMATION

Can	500 ml* 1 l
Container	5 l*

\* Not on stock in DK

## BASIS OF PRODUCT DATA

All technical data stated in this document are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## HEALTH AND SAFETY INFORMATION

For information and advice regarding transportation, handling, storage and disposal of chemical products, users shall refer to the actual Safety Data Sheets containing physical, ecological, toxicological and other safety-related data.

## DISCLAIMER

Any information or suggestions for use concerning Sika's products, which we either in writing or orally have given buyers or end-users of the product, have been given in good faith based on our own experiences and based on approved praxis and the technological and scientific knowledge on the time of giving such suggestions and information, which are given without any type of guarantees, and which do not lead to any further responsibility from Sika Danmark A/S, besides what is stated in the sales agreement in question. The buyer or end-user should themselves investigate or otherwise make sure, that our products are suitable for the use in question and further make sure that the products are kept and used correct and in agreement with the published rules and considering the actual conditions in order to avoid damages or less satisfactory results. Any order is accepted and any deliverance is affected according to the general terms of sales and delivery from Sika Danmark A/S, which are considered known and accepted, and which could be handed out when asked for. Our catalogues are not up-dated automatically. The present product data sheet is only for use in Denmark. Values stated in the present product data sheet should be seen as recommended, unless stated otherwise.

## PRODUCT DATA SHEET

Sika® Tooling Agent N  
Version 02.01 (03 - 2023), en\_DK  
019400000050001100

Sika Danmark A/S  
Hirsemarken 5  
3520 Farum  
Tlf. +45 48 18 85 85  
www.sika.dk

